

SPECIFICATIONS

QUALITY: A611 ARTISAN'S

COLORS:	2893 Parchment	2896 Mystic	2899 Silverado	2902 Fortuna
	2894 Brulee'	2897 Green Tea	2900 Windsor	2903 Chenille
	2895 Fling	2898 Pinehurst	2901 Canyon	2904 Crema
				2905 Mesa

**CONSTRUCTION
PILE FIBER**

Blue Sky® Technology – Tip Sheared
100% Antron Legacy Nylon with Dura Tech Soil
Resistance Treatment.

BENEFITS

DuraTech® soil resistant treatment provides superior soil
resistance durable for the useful life of the carpet. Antron® Legacy
carpet face fiber has a 30% lower Total Environmental Impact than
typical industry.

**YARN PLY
TUFTED YARN WEIGHT
TOTAL WEIGHT
MACHINE GAUGE
STITCHES PER INCH
FINISHED PILE THICKNESS
DENSITY FACTOR
CRI TRAFFIC RATING
WIDTH
PRIMARY BACKING
SECONDARY BACKING**

2 Ply
33 Ounces Per Sq. Yd. (1119 g/m²)
66 Oz. Approx.
1/12" (4.72 rows/cm)
13 (5.12 stitches/cm)
.155 Inch Approx. (3.973 mm)
7665
Heavy
12' (3.66m)
100% Synthetic
Power Lock® RE with minimum 10% post consumer recycled
content based on total product weight. Produced with LOMAX™
Technology, a renewable energy.
Average Critical Radiant Flux: Greater than .45 - Class 1
Specific Optical Density: Less than 450
Impressionist, Performing Arts
Qualifies for Blueridge Blue Cycle Reclamation Program

**ASTM E-648
NBS SMOKE CHAMBER TEST
COORDINATE PRODUCTS
RECYCLING PROGRAM**

Produced with LOMAX™
Technology, a renewable energy.
Average Critical Radiant Flux: Greater than .45 - Class 1
Specific Optical Density: Less than 450
Impressionist, Performing Arts
Qualifies for Blueridge Blue Cycle Reclamation Program

WARRANTIES:

WEAR WARRANTY	Useful Life
STATIC WARRANTY	Useful Life
EDGE RAVEL GUARANTEE	Useful Life
DELAMINATION GUARANTEE	Useful Life

CRI Green Label Plus Indoor Air Quality Testing Program - Passes - Certification No. GLP 2878

NOTES:

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step® walk-off tiles by Blue Ridge or walk-off mats are recommended at building entryways to reduce soiling.

Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber, fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture". Performance is not affected by these variables

Due to the nature of patterned textile products, an exact pattern match cannot be guaranteed. Some visual inconsistencies in the surface appearance of all textile products should be expected, including visible seams. This product, Artisan's, requires the row cut/row cut seaming technique in order to produce quality seams. Seam sealer must be used.

Installation of pattern carpet requires more time to install correctly, which should be considered in the original installation quotation. Carpet must be installed according to manufacturer's installation procedures.