

SPECIFICATIONS

S.O.P. 500 sq. yd. min.

QUALITY: A900 AXIOM

COLORS:	2703 Ivory	2709 Graphite	2715 Moss	2052 Stone
	2704 Nickel	2710 Glacier	2039 Dusk	2054 Gravel
	2705 Malt	2711 Deep Sea	2041 Storm	2056 Walnut
	2706 Cedar	2712 Linden	2042 Dune	2059 Java
	2707 Oxblood	2713 Hemlock	2047 Cashmere	2428 Bracken
	2708 Thistle	2714 Citrine	2050 Port	2429 Pacific

- CONSTRUCTION - Multi-Level Loop
- PILE FIBER - 100% Antron Legacy Nylon with Dura Tech Soil Resistance Treatment.
- YARN PLY - 4 Ply
- TUFTED YARN WEIGHT - 40 Ounces Per Sq. Yd. (1356 g/m²)
- MACHINE GAUGE - 5/30" (2.36 rows/cm)
- STITCHES PER INCH - 9.2 (3.54 stitches/cm)
- AVERAGE TUFTED PILE HEIGHT - .234 Inch Approx. (5.46 mm)
- DENSITY FACTOR - 6154
- WIDTH - 12' (3.66m)
- PRIMARY BACKING - 100% Synthetic
- SECONDARY BACKING - Power Lock® RE with minimum 10% post consumer recycled content based on total product weight. Produced with LOMAX™ Technology, a renewable energy.
- ASTM E-648 - Average Critical Radiant Flux: Greater than .45 - Class 1
- NBS SMOKE CHAMBER TEST - Specific Optical Density: Less than 450
- COORDINATE PRODUCTS - Foundation

- WARRANTIES:
- Wear Warranty - Useful Life
- Static Warranty - Useful Life
- Edge Ravel Guarantee - Useful Life
- Delamination Guarantee - Useful Life
- Recycling - Qualifies for Blueridge Blue Cycle Reclamation Program

CRI Green Label Plus Indoor Air Quality Testing Program - Passes - Certification No. GLP 2878

NOTES:

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step® walk-off tiles by Blue Ridge or walk-off mats are recommended at building entryways to reduce soiling.

Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber, fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture". Performance is not affected by these variables

As with all patterned carpet, a perfect pattern match may not be possible due to the fact that carpet is a textile subject to shrinking and expansion in both length and width. A plus or minus 1% should be expected. However, a reasonable pattern match may be achieved by competent installers using power stretching and stay nailing techniques.

Installation of pattern carpet requires more time to install correctly, which should be considered in the original installation quotation.