

SPECIFICATIONS

QUALITY: **H308T HARMONY** 24" X 24" Carpet Tile
 H308V HARMONY 6 Ft. EnviroFlex®

COLORS: (32)	3157 Shale	3165 Alpine	3173 Bacchus	3181 Chaparral
	3158 Truffle	3166 Caribe	3174 Koala	3182 Sunrise
	3159 Tumbleweed	3167 Serenade	3175 Mahogany	3183 Gilded
	3160 Lunar	3168 Pinto	3176 Zither	3184 Wicker
	3161 Bali	3169 Briquette	3177 Linen	3185 Briar
	3162 Glass	3170 Licorice	3178 Kraft	3186 Kiwi
	3163 Denim	3171 Oxford	3179 Onyx	3187 Capricious
	3164 Spa	3172 Tangy	3180 Decaf	3188 Midnight

CONSTRUCTION	-	Multi-Level Pattern Loop
YARN	-	100% Antron Lumena® Solution Dyed Nylon with Dura Tech® Soil Resistant Treatment and Recycled Content
DYE METHOD	-	Solution Dyed
PRIMARY BACKING	-	100% Synthetic
SECONDARY BACKING	-	EnviroFlex® Performance Engineered Backing w/40% Recycled Content
TUFTED YARN WEIGHT	-	24 Ounces Per Sq. Yd. (814 g/m²)
FINISHED PILE THICKNESS	-	Approx. .126 Inch (3.2mm)
DENSITY FACTOR	-	6857
STITCHES PER INCH	-	10 (3.94 stitches/cm)
MACHINE GAUGE	-	1/12" (4.72 rows/cm)
CRI TRAFFIC RATING	-	Severe
TILE SIZE	-	24" X 24" (60.96 cm X 60.96 cm)
ROLL WIDTH	-	6 Ft. (1.83 m)
PATTERN REPEAT	-	Not Required – W x 23" L (58.42 cmL)
ADHESIVE	-	BR200 EnviroFlex® Modular Carpet Adhesive
COORDINATE PRODUCTS	-	Guidelines, Poetic, Transitions, Verbatim

Installation	-	Monolithic, Brick or ¼ Turn
Wear Warranty	-	10 Year
Edge Ravel Guarantee	-	Useful Life
Delamination Guarantee	-	Useful Life
Run Resistance Warranty	-	Useful Life
Stain Removal Guarantee	-	Useful Life
Static Warranty	-	Useful Life
Colorfastness to Light	-	10 Year
Colorfastness to Atmospheric Contaminants	-	5 Year
Recycling Program	-	Qualifies for the Blueridge BlueCycle Reclamation Program

CRI Green Label Plus Indoor Air Quality Testing Program – Passes – Certification No. GLP 9712

NOTES:

Due to the nature of modular patterned textile products, an exact pattern match cannot be guaranteed. Some visual inconsistencies in the surface appearance of all textile products should be expected, including visible seams.

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. CleanStep® Walk Off Tiles by Blueridge or walk off mats are recommended at building entryways to reduce soiling.

Product specifications are derived from averages resulting from normal manufacturing tolerance in yarn fiber, fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture." Performance is not affected by these variables.

Carpet must be installed according to manufacturer's carpet installation procedures. This product requires a double cut slight serpentine seaming technique to produce quality seams with 6 ft. rolls. Seam sealer must be used.