

SPECIFICATIONS

QUALITY: H308 HARMONY BROADLOOM

COLORS: (32)	3214 Oxford	3222 Shale	3230 Truffle	3238 Kiwi
	3215 Tangy	3223 Linen	3231 Sunrise	3239 Denim
	3216 Pinto	3224 Lunar	3232 Gilded	3240 Caribe
	3217 Bacchus	3225 Kraft	3233 Glass	3241 Bali
	3218 Briquette	3226 Onyx	3234 Wicker	3242 Capricious
	3219 Koala	3227 Decaf	3235 Spa	3243 Serenade
	3220 Mahogany	3228 Licorice	3236 Tumbleweed	3244 Alpine
	3221 Zither	3229 Chaparral	3237 Briar	3245 Midnight

CONSTRUCTION	-	Multi-Level Pattern Loop
YARN	-	100% Antron Lumena® Solution Dyed Nylon with Dura Tech® Soil Resistant Treatment and Recycled Content
DYE METHOD	-	Solution Dyed
PRIMARY BACKING	-	100% Synthetic
SECONDARY BACKING	-	Power Lock® RE with min. 10% post consumer recycled content based on total product weight. Produced with LOMAX™ Technology, a renewable energy.
TUFTED YARN WEIGHT	-	26 Ounces Per Sq. Yd. (881 g/m²)
STITCHES PER INCH	-	10 (3.94 stitches/cm)
FINISHED PILE THICKNESS	-	Approx. .126 Inch (3.28 mm)
WEIGHT DENSITY	-	7429
MACHINE GAUGE	-	1/12" (4.72 rows/cm)
CRI TRAFFIC RATING	-	Heavy
WIDTH	-	12 Ft. (3.66 m)
PATTERN REPEAT	-	24" W x 23" L (60.96 cm W x 58.42 cm L)
COORDINATE PRODUCTS	-	Contributor, Critic's Choice

Wear Warranty	-	10 Year
Edge Ravel Guarantee	-	Useful Life
Delamination Guarantee	-	Useful Life
Run Resistance Warranty	-	Useful Life
Stain Removal Guarantee	-	Useful Life
Static Warranty	-	Useful Life
Colorfastness to Light	-	10 Year
Colorfastness to Atmospheric Contaminants	-	5 Year
Recycling Program	-	Qualifies for the Blueridge Blue Cycle Reclamation Program

CRI Green Label Plus Indoor Air Quality Testing Program – Passes – Certification No. GLP 4078

NOTES:

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. CleanStep® Walk Off Tiles by Blueridge or walk off mats are recommended at building entryways to reduce soiling.

Product specifications are derived from averages resulting from normal manufacturing tolerance in yarn fiber, fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture." Performance is not affected by these variables.

As with all patterned carpet, a perfect pattern match may not be possible due to the fact that carpet is a textile subject to shrinking and expansion in both length and width. A plus or minus 1% should be expected. However, a reasonable pattern match may be achieved by competent installers using power stretching and stay nailing techniques.

Carpet must be installed according to manufacturer's carpet installation procedures. This product requires a row cut seaming technique to produce quality seams. Seam sealer must be used.