

**SPECIFICATIONS**

**QUALITY: I410 IMPRESSIONIST**

<b>COLORS:</b>	2893 Parchment	2896 Mystic	2899 Silverado	2902 Fortuna
	2894 Brulee'	2897 Green Tea	2900 Windsor	2903 Chenille
	2895 Fling	2898 Pinehurst	2901 Canyon	2904 Crema
				2905 Mesa

<b>CONSTRUCTION</b>	Blue Sky® Technology – Tip Sheared
<b>PILE FIBER</b>	100% Antron Legacy Nylon with Dura Tech Soil Resistance Treatment.
<b>BENEFITS</b>	DuraTech® soil resistant treatment provides superior soil resistance durable for the useful life of the carpet. Antron® Legacy carpet face fiber has a 30% lower Total Environmental Impact than typical industry.
<b>YARN PLY</b>	2 Ply
<b>TUFTED YARN WEIGHT</b>	33 Ounces Per Sq. Yd. (1119 g/m²)
<b>TOTAL WEIGHT</b>	66 Oz. Approx.
<b>MACHINE GAUGE</b>	1/12" (4.72 rows/cm)
<b>STITCHES PER INCH</b>	13 (5.12 stitches/cm)
<b>FINISHED PILE THICKNESS</b>	.202 Inch Approx. (0.513 mm)
<b>DENSITY FACTOR</b>	5881
<b>CRI TRAFFIC RATING</b>	Heavy
<b>WIDTH</b>	12' (3.66m)
<b>PRIMARY BACKING</b>	100% Synthetic
<b>SECONDARY BACKING</b>	Power Lock® RE with minimum 10% post consumer recycled content based on total product weight. Produced with LOMAX™ Technology, a renewable energy.
<b>ASTM E-648</b>	Average Critical Radiant Flux: Greater than .45 - Class 1
<b>NBS SMOKE CHAMBER TEST</b>	Specific Optical Density: Less than 450
<b>COORDINATE PRODUCTS</b>	Performing Arts, Artisan's
<b>RECYCLING PROGRAM</b>	Qualifies for Blueridge Blue Cycle Reclamation Program

**WARRANTIES:**

Wear Warranty	Useful Life
Static Warranty	Useful Life
Edge Ravel Guarantee	Useful Life
Delamination Guarantee	Useful Life

**CRI Green Label Plus Indoor Air Quality Testing Program - Passes - Certification No. GLP 2878**

**NOTES:**

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step® walk-off tiles by Blue Ridge or walk-off mats are recommended at building entryways to reduce soiling.

Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber, fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture". Performance is not affected by these variables

Due to the nature of patterned textile products, an exact pattern match cannot be guaranteed. Some visual inconsistencies in the surface appearance of all textile products should be expected, including visible seams. This product, Impressionist, requires the row cut/row cut seaming technique in order to produce quality seams. Seam sealer must be used.

Installation of pattern carpet requires more time to install correctly, which should be considered in the original installation quotation. Carpet must be installed according to manufacturer's installation procedures.