

SPECIFICATIONS

QUALITY: P216 PATHWAYS

COLORS:	2752 Glen Burney	2756 Hawks Bill	2760 Iron Mountain
	2753 Doughton Park	2757 Crabtree Meadows	2761 Elk River
	2754 Gum Tree	2758 Timber Ridge	2762 Air Bellows
	2755 Lost Cove	2759 Flattop Mountain	2763 Fontana Lake

CONSTRUCTION	Multi Level Pattern Loop
PILE FIBER	100% Antron Lumena® Solution Dyed Nylon with Dura Tech Soil Resistance Treatment and Recycled Content.
DYE METHOD	Solution Dyed
TUFTED YARN WEIGHT	28 Ounces Per Sq. Yd. (949 g/m ²)
TOTAL WEIGHT	Approx. 73 Oz. (2475 g/m ²)
MACHINE GAUGE	1/12" (4.72 rows/cm)
STITCHES PER INCH	13 (5.12 stitches/cm)
FINISHED PILE THICKNESS	.167 Inch Approx. (4.24 mm)
DENSITY FACTOR	6036
WIDTH	12' (3.66m)
PRIMARY BACKING	100% Synthetic
SECONDARY BACKING	Power Lock® RE with minimum 10% post consumer recycled content based on total product weight. Produced with LOMAX™ Technology, a renewable energy.
ASTM E-648	Average Critical Radiant Flux: Greater than .45 - Class 1
NBS SMOKE CHAMBER TEST	Specific Optical Density: Less than 450
COORDINATE PRODUCTS	Traveler Modular
RECYCLING PROGRAM	Qualifies for Blueridge Blue Cycle Reclamation Program
PATTERN REPEAT	24" W x 25" L (61.96 cm W x 63.5 cm L)
CRI TRAFFIC RATING	Severe

WARRANTIES:

WEAR WARRANTY	Useful Life
RUN RESISTANCE	Useful Life
STATIC WARRANTY	Useful Life
EDGE RAVEL GUARANTEE	Useful Life
DELAMINATION GUARANTEE	Useful Life
COLORFASTNESS TO LIGHT	10 Years
COLORFASTNESS TO ATMOSPHERIC CONTAMINANTS	5 Years

CRI Green Label Plus Indoor Air Quality Testing Program - Passes - Certification No. GLP 4078

NOTES:

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step walk-off tiles by Blue Ridge or walk-off mats are recommended at building entryways to reduce soiling.

Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber, fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture". Performance is not affected by these variables

As with all patterned carpet, a perfect pattern match may not be possible due to the fact that carpet is a textile subject to shrinking and expansion in both length and width. A plus or minus 1% should be expected. However, a reasonable pattern match may be achieved by competent installers using power stretching and stay nailing techniques.

Installation of pattern carpet requires more time to install correctly, which should be considered in the original



Blue Ridge Commercial Carpet P.O. Box 507, Ellijay, GA 30540
800 354 8951, 706 276 2005, www.blueridgecarpet.com

installation quotation.