

***SPECIFICATIONS**

QUALITY: **S-070 SANTA FE** - Synthetic Power-Lock® High Performance Backing System

COLORS: (13)	2668 Galleries	2671 Alley Way	2674 Pacific	2677 Indian Market
	2669 Rockies	2672 Royal Road	2675 Point Lobos	2678 Mission Basilica
	2670 Headlands	2673 Ocean Avenue	2676 Adobe	2679 Pueblos
				2680 Cliff Dwellings

CONSTRUCTION	Multi-Level Pattern Loop Featuring Blue Sky® Technology
PILE FIBER	80% Zeftron Solure enviro6ix® Nylon contains a minimum of 25% recycled content/20% Zeftron Select Yarn Dyed Nylon. Treated with Blue Shield® stain and soil protector.
DYE METHOD	80%Solution Dyed/20%Yarn Dyed
PRIMARY BACKING	100% Synthetic
SECONDARY BACKING	Power Lock® RE w/ minimum 10% post consumer recycled content based on total product weight
YARN PLY	3 Ply & 2 Ply
TUFTED YARN WEIGHT	28 Oz. per Sq. Yd. (949 g/m ²)
FINISHED PILE THICKNESS	.157 Inch Approx. (3.99 mm)
STITCHES PER INCH	10 (3.93 stitches/cm)
MACHINE GAUGE	1/12" (4.72 rows/cm)
DENSITY FACTOR	6420
TRAFFIC CLASS	Extra Heavy Commercial Class III
CARPET WIDTH	12' (3.66 m)
PATTERN REPEAT	18" W x 12" L (45.72 cm W x 30.48 cm L)
DYE LOT SIZE	20,000 Square Yards
FLAMMABILITY	ASTM E-648 – Class I NFPA 258 – 450 or Less
RECYCLING PROGRAM	Qualifies for 6ix® Again Program

WARRANTIES:

EDGE RAVEL GUARANTEE	Useful Life
DELAMINATION GUARANTEE	Useful Life
RUN RESISTANCE WARRANTY	Useful Life
STATIC WARRANTY	Useful Life

CRI Green Label Plus Indoor Air Quality Testing Program - Passes - Certification No. GLP 4078

NOTES:

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step® Walk-Off Tiles by Blue Ridge or Walk-off mats are recommended at building entryways to reduce soiling.

Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber, fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture". Performance is not affected by these variables

Due to the nature of patterned textile products, an exact pattern match cannot be guaranteed. Some visual inconsistencies in the surface appearance of all textile products should be expected, including visible seams. This product, Santa Fe, requires the row cut seaming technique in order to product quality seams. Patterned carpet may require special attention by the installer to assure a suitable match and must be addressed in the original labor quotation. Seam sealer must be used. Carpet must be installed according to manufacturer's installation procedures.