

**\*SPECIFICATIONS**

**QUALITY:** T-300T TECO 24" X 24" Carpet Tile

<b>COLORS:</b>	3000 Porcelain	3005 Brown Patina	3009 Cast Brass	3013 Pewter
	3001 Stained Mica	3006 Ash Wood	3010 Cucumber Glaze	3014 Silver
	3002 Wood	3007 Leaded Glass	3011 Slate	3015 Textile Blue
	3003 Oak	3008 Leather	3012 Metal	3016 Cast Iron
	3004 Copper			

CONSTRUCTION	Multi-Level Pattern Loop
PILE FIBER	100% Antron Lumena Nylon with Dura Tech Soil Resistance Treatment.
BENEFITS	DuraTech® soil resistant treatment provides superior soil resistance durable for the useful life of the carpet. Antron® Legacy carpet face fiber has a 30% lower Total Environmental Impact than typical industry.
TUFTED YARN WEIGHT	20 Ounces Per Sq. Yd. (678 g/m <sup>2</sup> )
TOTAL WEIGHT	140 Oz. Approx.
MACHINE GAUGE	1/12" (4.72 rows/cm)
STITCHES PER INCH	10 (3.94 stitches/cm)
FINISHED PILE THICKNESS	.092 Inch Approx. (2.37 mm)
DENSITY FACTOR	7826
CARPET TILE SIZE	24" x 24" Carpet Tile (60.96 cm x 60.96 cm)
PRIMARY BACKING	100% Synthetic
SECONDARY BACKING	EnviroFlex® Performance Engineered Backing w/40% Recycled Content
ASTM E-648	Average Critical Radiant Flux: Greater than .45 - Class 1
NBS SMOKE CHAMBER TEST	Specific Optical Density: Less than 450
COORDINATE PRODUCTS	Elmslie, Oak Park, Spindle Back
RECYCLING PROGRAM	Qualifies for the Invista Reclamation Program
ADHESIVE	BR200 EnviroFlex® Modular Carpet Adhesive

**WARRANTIES:**

WEAR WARRANTY	Useful Life
STATIC WARRANTY	Useful Life
EDGE RAVEL GUARANTEE	Useful Life
DELAMINATION GUARANTEE	Useful Life
RUN RESISTANCE WARRANTY	Useful Life
COLORFASTNESS TO LIGHT	10 Year
COLORFASTNESS TO ATMOSPHERIC CONTAMINANTS	5 Year

**CRI Green Label Plus Indoor Air Quality Testing Program - Passes - Certification No. GLP 9712**

**NOTES:**

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step® walk-off tiles by Blue Ridge or walk-off mats are recommended at building entryways to reduce soiling.

\*Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber, fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture". Performance is not affected by these variables

Due to the nature of modular patterned textile products, an exact pattern match cannot be guaranteed. Some visual inconsistencies in the surface appearance of all textile products should be expected, including visible seams.

Installation of pattern carpet requires more time to install correctly, which should be considered in the original installation quotation. Carpet must be installed according to manufacturer's installation procedures.