

Effective Date: June 4, 2004

*SPECIFICATIONS

QUALITY: A-190T ANCIENT WRITING 24" x 24" Carpet Tile

COLORS:	2535 Warp	2539 Culture
	2536 Weft	2540 Values
	2537 Indigo	2541 Wool
	2538 Stories	2542 Legends

CONSTRUCTION	-	Multi-Level Pattern Loop
YARN	-	100% Zeftron® Solure Nylon Enviro6ix contains a minimum of 25% post industrial and/or post consumer recycled content. Treated with a stain protector and a soil repellent.
DYE METHOD	-	Solution Dyed
PRIMARY BACKING	-	100% Synthetic
SECONDARY BACKING	-	EnviroFlex® Performance Engineered Backing with 40% Recycled Content
YARN PLY	-	2 Ply
TUFTED YARN WEIGHT	-	19 ozs. per sq. yd. (644 g/m ²)
TOTAL WEIGHT	-	142 ozs. per sq. yd. (4815 g/m ²)
FINISHED PILE THICKNESS	-	Approximately .105 inch (2.67 mm)
STITCHES PER INCH	-	10 (3.94 stitches/cm)
MACHINE GAUGE	-	1/12" (4.72 rows/cm)
DENSITY	-	6,514
TILE SIZE	-	24" x 24" (60.96 cm x 60.96 cm)
TRAFFIC CLASS	-	Extra Heavy Commercial Class III
DYE LOT SIZE	-	20,000 square yards
ADHESIVES	-	CA02V Vinyl Carpet Adhesive

Installation	-	All Installation Methods Acceptable
Wear Warranty	-	Useful Life
Edge Ravel Guarantee	-	Useful Life
Delamination Guarantee	-	Useful Life
Run Resistance Warranty	-	Useful Life
Stain Removal Guarantee	-	Useful Life
Static Warranty	-	Useful Life
Colorfastness to Light	-	Useful Life
Colorfastness to Atmospheric Contaminants	-	Useful Life
Recycling Program	-	Qualifies for 6ix™ Again Program

CRI – INDOOR AIR QUALITY TESTING PROGRAM – PASSES – CERTIFICATION NO. 34679712

NOTES:

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear out. Clean Step® Walk-off tiles by Blue Ridge are recommended at building entryways to reduce soiling.

Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture". Performance is not affected by these variables.

Due to the nature of modular patterned textile products, an exact pattern match cannot be guaranteed. Some visual inconsistencies in the surface appearance of all textile products should be expected, including visible seams.

Carpet should be installed according to manufacturer's carpet installation procedures.