Blueridge RICHMOND

Effective Date: June 14, 2007

*SPECIFICATIONS

QUALITY: **5600 ARCHES - Quick Ship**

COLORS:

5601 Tiger Eye	5604 Green Tea
5602 Charcoal	5605 Wren
5603 Spice	5606 Thrasher

CONSTRUCTION	-	Tufted Multi-Level Loop
YARN	-	SEP* Solution Dyed and Yarn Dyed Continuous Filament Nylon with Antistat
TUFTED YARN WEIGHT	-	24 Ounces (814g/m²)
MACHINE GAUGE	-	1/10" (3.94 rows/cm)
STITCHES PER INCH	-	11 (4.33 stitches/cm)
FINISHED PILE THICKNESS	-	.144 (3.65 mm)
WIDTH	-	12 ft. (3.66 m)
DYE METHOD	-	75% Solution Dyed / 25% Yarn Dyed
SOIL / STAIN PROTECTION	-	Blue Shield® Soil and Stain Protector
DENSITY	-	6000
PRIMARY BACKING	-	Woven Polypropylene
SECONDARY BACKING	-	Woven Synthetic
RADIANT PANEL TEST	-	Class I
NBS SMOKE CHAMBER TEST	-	Passes
PATTERN REPEAT	-	½" W x ½" L (1.27 cm x 1.27 cm)
AVERAGE DELIVERY	-	Two Weeks**
OPTIONAL BACKINGS	-	High tuft-bind woven synthetic, moisture barrier backings and attached polyurethane cushions available.Contact mill for details.
WARRANTIES	-	10-Year Wear Warranty 10-Year Delamination Warranty 10-Year Edge Ravel Warranty

CRI Green Label Plus Indoor Air Quality Testing Program - Passes – Certification No. 4078

NOTES:
Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step® walk-off tiles or walk-off mats are recommended at building entryways to reduce soiling.

Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture." Performance is not affected by these variables.

Some visual inconsistencies in the surface appearance of all textile products should be expected, including visible seams. This product requires the row cut seaming technique in order to produce quality seams. Seam sealer must be used.

Carpet should be installed according to manufacturer's carpet installation procedures.

*S.E.P. Nylon is: Solution dyed Environmentally Positive nylon by Richmond Carpet Company. SEP nylon is produced using environmentally friendly pigments and is recyclable.

**Ten working days from date of credit approval.

Blue Ridge Industries PO Box 507, Ellijay, Georgia 30540
706 276 2001, fax 706 276 2005, www.blueridgecarpet.com