

SPECIFICATIONS

QUALITY: A600 ARTEMIS

COLORS: (20)	2621 Constellation	2626 Great Bear	2632 Countryside	2637 Leto
	2622 Selene	2627 Mountain	2633 Bow	2638 Guardian
	2623 Sparta	2628 Wilderness	2634 Hunting	2639 Lion
	2624 Moon	2629 Giant	2635 Pool	2640 Twin
	2625 Goddess	2631 Arrows	2636 Delos	2641 Stag

CONSTRUCTION	Stitch Lock™ Technology – Minimum ¾” Step-Over
PILE FIBER	100% Zeftron Solure enviro6ix® Nylon contains a minimum of 25% recycled content. Treated with Blue Shield® stain and soil protector.
DYE METHOD	Solution Dyed
PRIMARY BACKING	100% Synthetic
SECONDARY BACKING	Power Lock® RE with minimum 10% post consumer recycled content based on total product weight. Produced with LOMAX™ Technology, a renewable energy.
YARN PLY	3 Ply
TUFTED YARN WEIGHT	28 Oz. per Sq. Yd. (949 g/m²)
FINISHED PILE THICKNESS	114 Inch Approx. (2.90 mm)
STITCHES PER INCH	10 (3.94 stitches/cm)
MACHINE GAUGE	1/10 (3.94 rows/cm)
DENSITY FACTOR	8842
TRAFFIC CLASS	Extra Heavy Commercial Class III
CARPET WIDTH	12' (3.66 m)
DYE LOT SIZE	20,000 Square Yards
VETTERMAN DRUM-WEAR	3-4 or better after 22,000 cycles - ASTM 5417
DELAMINATION	2.70 Lbs/Inch or Greater - ASTM D3936
LIGHT FASTNESS	4 or Better After 8 Cycles of Exposure - AATCC 16
OZONE	4 or Better After 8 Cycles of Exposure - AATCC 129
OXIDES OF NITROGEN	4 or Better After 8 Cycles of Exposure - AATCC 164
FLAMMABILITY	ASTM E-648 – Class I NFPA 258 – 450 or Less
RECYCLING PROGRAM	Qualifies for Blueridge Blue Cycle Reclamation Program

WARRANTIES:

EDGE RAVEL GUARANTEE	Useful Life
DELAMINATION GUARANTEE	Useful Life
RUN RESISTANCE WARRANTY	Useful Life
WEAR WARRANTY	Useful Life
STAIN REMOVAL GUARANTEE	Useful Life
STATIC WARRANTY	Useful Life
COLORFASTNESS TO LIGHT	Useful Life
COLORFASTNESS TO ATMOSPHERIC CONTAMINANTS	Useful Life

CRI Green Label Plus Indoor Air Quality Testing Program - Passes - Certification No. GLP 4078

NOTES:

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step walk-off tiles by Blue Ridge or walk-off mats are recommended at building entryways to reduce soiling.

Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber, fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture". Performance is not affected by these variables.

Artemis requires the row cut / trace cut seaming technique in order to produce quality seams. Seam sealer must be used.

Carpet must be installed according to manufacturer's carpet installation procedures.