Blue Ridge Commercial Carpet P.O. Box 507, Ellijay, GA 30540
800 354 8951, 706 276 2005, www.blueridgecarpet.com

SPECIFICATIONS

QUALITY: **B150T BARGELLO** 24" X 24" Carpet Tile

COLORS:

2396 Russet	2400 Silver Leaf
2397 Maple	2401 Toccoa River
2398 Oak Ridge	2402 Pine
2399 Appalachian	2403 Ellijay

CONSTRUCTION	-	Multi-Level Pattern Loop
YARN	-	100% Zeftron® Solure Nylon contains recycled content. Treated with Blue Shield® soil and stain protector.
DYE METHOD	-	Solution Dyed
PRIMARY BACKING	-	100% Synthetic
SECONDARY BACKING	-	EnviroFlex® Performance Engineered Backing w/40% Recycled Content
YARN PLY	-	2 Ply
TUFTED YARN WEIGHT	-	20 Ounces Per Sq. Yd. (678 g/m²)
TOTAL WEIGHT	-	144 Ounces Per Sq. Yd. (4883 g/m²)
FINISHED PILE THICKNESS	-	Approximately .090 inch (2.29 mm)
STITCHES PER INCH	-	10 (3.94 stitches/cm)
MACHINE GAUGE	-	1/12" (4.72 rows/cm)
DENSITY	-	8000
TILE SIZE	-	24" X 24" (60.96 cm X 60.96 cm)
TRAFFIC CLASS	-	Extra Heavy Commercial Class III
DYE LOT SIZE	-	20,000 Square Yards
LIGHT FASTNESS	-	4 or Better After 8 Cycles of Exposure – AATCC 16
OZONE	-	4 or Better After 8 Cycles of Exposure – AATCC 129
OXIDES OF NITROGEN	-	4 or Better After 8 Cycles of Exposure – AATCC 164
ADHESIVE	-	BR200 EnviroFlex® Modular Carpet Adhesive

Installation	-	¼ Turn or Brick
Wear Warranty	-	Useful Life
Edge Ravel Guarantee	-	Useful Life
Delamination Guarantee	-	Useful Life
Run Resistance Warranty	-	Useful Life
Stain Removal Guarantee	-	Useful Life
Static Warranty	-	Useful Life
Colorfastness to Light	-	Useful Life
Colorfastness to Atmospheric Contaminants	-	Useful Life
Recycling Program	-	Qualifies for Blueridge Blue Cycle Reclamation Program

CRI Green Label Plus Indoor Air Quality Testing Program – Passes – Certification No. GLP 9712

NOTES:
Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step® walk-off tiles or walk-off mats are recommended at building entryways to reduce soiling.

Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture". Performance is not affected by these variables

Due to the nature of modular patterned textile products, an exact pattern match cannot be guaranteed. Some visual inconsistencies in the surface appearance of all textile products should be expected, including visible seams.

Carpet should be installed according to manufacturer's carpet installation procedures.