

Revised Date: January 11, 2006

*SPECIFICATIONS

QUALITY: B-155 BASIS

COLORS:	2703 Ivory	2709 Graphite	2715 Moss	2052 Stone
	2704 Nickel	2710 Glacier	2039 Dusk	2054 Gravel
	2705 Malt	2711 Deep Sea	2041 Storm	2056 Walnut
	2706 Cedar	2712 Linden	2042 Dune	2059 Java
	2707 Oxblood	2713 Hemlock	2047 Cashmere	2428 Bracken
	2708 Thistle	2714 Citrine	2050 Port	2429 Pacific

CONSTRUCTION	-	Precision Cut and Uncut
PILE FIBER	-	100% Antron Legacy Nylon with Dura Tech Soil Resistance Treatment.
YARN PLY	-	2 & 3 Ply
TUFTED YARN WEIGHT	-	40 Ounces Per Sq. Yd. (1356 g/m ²)
TOTAL WEIGHT	-	77 Oz.
MACHINE GAUGE	-	1/8" (3.15 rows/cm)
STITCHES PER INCH	-	13 (5.12 stitches/cm)
FINISHED PILE THICKNESS	-	.206 Inch Approx. (5.23 mm)
DENSITY FACTOR	-	6990
WIDTH	-	12' (3.66m)
PRIMARY BACKING	-	100% Synthetic
SECONDARY BACKING	-	Power Lock® High Performance Backing
ASTM E-648	-	Average Critical Radiant Flux: Greater than .45 - Class 1
NBS SMOKE CHAMBER TEST	-	Specific Optical Density: Less than 450
COORDINATE PRODUCTS	-	Axiom, Paradigm
RECYCLING PROGRAM	-	Qualifies for the Invista Reclamation Program

WARRANTIES:

WEAR WARRANTY	10 Year
STATIC WARRANTY	Useful Life
EDGE RAVEL GUARANTEE	Useful Life
DELAMINATION GUARANTEE	Useful Life

CRI Green Label Plus Indoor Air Quality Testing Program - Passes - Certification No. GLP 2878

NOTES:

1. Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step walk-off tiles by Blue Ridge or walk-off mats are recommended at building entryways to reduce soiling.
- 2.*Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber, fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture". Performance is not affected by these variables
3. As with all patterned carpet, a perfect pattern match may not be possible due to the fact that carpet is a textile subject to shrinking and expansion in both length and width. A plus or minus 1% should be expected. However, a reasonable pattern match may be achieved by competent installers using power stretching and stay nailing techniques.
4. Installation of pattern carpet requires more time to install correctly, which should be considered in the original installation quotation.