

Effective Date: September 17, 2003

*SPECIFICATIONS

QUALITY: B-208 BOUCLE' TWIST

COLORS:	2024 Oyster	2033 Mist	2042 Dune	2051 Shale
	2025 Khaki	2034 Celadon	2043 Straw	2052 Stone
	2141 Algae	2035 Teal	2044 Parchment	2053 Fog
	2027 Taupe	2036 Lavender	2045 Sienna	2054 Gravel
	2028 Dew	2037 Thistle	2046 Clay	2055 Loden
	2029 Eucalyptus	2038 Eggplant	2047 Cashmere	2056 Walnut
	2030 Cypress	2039 Dusk	2048 Rose Quartz	2057 Hazel
	2031 Olive	2040 Slate	2049 Raisin	2058 Earth
	2032 Laurel	2041 Storm	2050 Port	2059 Java

CONSTRUCTION	-	Enhanced Precision Cut and Uncut
PILE FIBER	-	100% Antron Legacy Nylon with Dura Tech Soil Resistance Treatment.
YARN PLY	-	2 Ply
TUFTED YARN WEIGHT	-	34 ozs. per sq. yd. (1153 g/m ²)
TOTAL WEIGHT	-	71 oz.
MACHINE GAUGE	-	1/8" (3.15 rows/cm)
STITCHES PER INCH	-	12 (4.72 stitches/cm)
FINISHED PILE THICKNESS	-	.229 Inch Approx. (5.82 mm)
DENSITY FACTOR	-	5,345
WIDTH	-	12' (3.66m)
PRIMARY BACKING	-	100% Synthetic
SECONDARY BACKING	-	Power Lock® High Performance Backing
ASTM E-648	-	Average Critical Radiant Flux: Greater than .45 - Class 1
NBS SMOKE CHAMBER TEST	-	Specific Optical Density: Less than 450
COORDINATE PRODUCTS	-	Foundation

WARRANTIES:

Wear Warranty	-	10 Years
Static Warranty	-	Useful Life
Edge Ravel Guarantee	-	Useful Life
Delamination Guarantee	-	Useful Life
Run Resistance Warranty	-	Useful Life
Recycling	-	Qualifies for the DuPont® Reclamation Program

CRI INDOOR AIR QUALITY TESTING PROGRAM – PASSES – CERTIFICATION NO. 14222878

NOTES:

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step® walk-off tiles by Blue Ridge or walk-off mats are recommended at building entryways to reduce soiling.

*Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber, fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture". Performance is not affected by these variables.

As with all patterned carpet, a perfect pattern match may not be possible due to the fact that carpet is a textile subject to shrinking and expansion in both length and width. A plus or minus 1% should be expected. However, a reasonable pattern match may be achieved by competent installers using power stretching and stay nailing techniques.

Installation of pattern carpet requires more time to install correctly, which should be considered in the original installation quotation.