

SPECIFICATIONS

QUALITY: C109 CACHE

COLORS: (16)	2768 <i>Nouveau</i>	2801 <i>Cranberry</i>	2816 <i>Sante Fe</i>	2834 <i>Mercury</i>
	2777 <i>Maple Sugar</i>	2802 <i>Lipstick</i>	2817 <i>Spanish Tile</i>	2836 <i>Basalt</i>
	2778 <i>Gaelic</i>	2805 <i>Cidar</i>	2824 <i>Zinc</i>	2837 <i>Thunder</i>
	2787 <i>Indigo</i>	2808 <i>Espresso</i>	2825 <i>Burnt Ivory</i>	2839 <i>Halite</i>

CONSTRUCTION	Blue Sky® Technology - Tip Sheared
PILE FIBER	100% Antron Legacy Nylon with DuraTech® Soil Resistance Treatment
BENEFITS	Antron® Legacy carpet face fiber has been certified by Scientific Certification Systems as an Environmentally Preferable Product.
TUFTED YARN WEIGHT	33 Ounces Per Sq. Yd. (1119 g/m ²)
MACHINE GAUGE	1/12" (4.72 rows/cm)
STITCHES PER INCH	12 (4.72 stitches/cm)
FINISHED PILE THICKNESS	.146 Inch Approx. (4.47 mm)
DENSITY FACTOR	8137
WIDTH	12' (3.66m)
PRIMARY BACKING	100% Synthetic
SECONDARY BACKING	Power Lock® RE w/ minimum 10% post consumer recycled content based on total product weight. Produced with LOMAX™ Technology, a renewable energy.
ASTM E-648	Average Critical Radiant Flux: Greater than .45 - Class 1
NBS SMOKE CHAMBER TEST	Specific Optical Density: Less than 450
COORDINATE PRODUCTS	Art & Soul Collection, Artful Endeavors Collection, Camaraderie Collection, Gatsby Collection, Great Inspirations, Marathon
PATTERN REPEAT	18" W x 35" L (45.72 cm W x 88.90 cm L)
CUSTOM COLORS	Available 60 Sq. Yd. Min per Color
RECYCLING PROGRAM	Qualifies for Blueridge Blue Cycle Reclamation Program
WARRANTIES:	
WEAR WARRANTY	10 Year
STATIC WARRANTY	Useful Life
EDGE RAVEL GUARANTEE	Useful Life
DELAMINATION GUARANTEE	Useful Life

CRI Green Label Plus Indoor Air Quality Testing Program - Passes - Certification No. GLP 2878

NOTES:

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step® Walk-Off Tiles by Blue Ridge or Walk-off mats are recommended at building entryways to reduce soiling.

Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber, fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture". Performance is not affected by these variables

Due to the nature of patterned textile products, an exact pattern match cannot be guaranteed. Some visual inconsistencies in the surface appearance of all textile products should be expected, including visible seams. This product, Cache, requires the row cut seaming technique in order to product quality seams. Patterned carpet may require special attention by the installer to assure a suitable match and must be addressed in the original labor quotation. Seam sealer must be used. Carpet must be installed according to manufacturer's installation procedures.