

SPECIFICATIONS

QUALITY: 3400 CARNIVAL

COLORS:	3401 Reflections	3406 Desert Tan
	3402 Parakeet	3407 Weathered Pine
	3403 Ember Glow	3408 Mountain Wood
	3404 Rainforest	3409 Jewel Tone
	3405 Crystal Palace	3410 Blue Oasis

- CONSTRUCTION** - Tufted Pattern Loop
- YARN** - 100% SEP* Nylon with Antistat
- TUFTED YARN WEIGHT** - 26 Ounces (882g/m²)
- MACHINE GAUGE** - 1/10" (3.94 rows/cm)
- STITCHES PER INCH** - 10 (3.94 stitches/cm)
- FINISHED PILE THICKNESS** - .133 (3.38 mm)
- DYE METHOD** - 75% Solution Dyed / 25% Space Dyed
- SOIL /STAIN PROTECTION** - Blue Shield® Soil and Stain Protector
- DENSITY** - 7,038
- PRIMARY BACKING** - Woven Polypropylene
- SECONDARY BACKING** - Woven Synthetic
- RADIANT PANEL TEST** - Class I
- NBS SMOKE CHAMBER TEST** - Passes
- PATTERN REPEAT** - ½" W x 1 ½" L (1.27cm W x 3.81cm L)
- COORDINATING STYLES** - The Americana Series
- RECYCLING PROGRAM** - Qualifies for Blueridge Blue Cycle Reclamation Program
- OPTIONAL BACKINGS** - High tuft-bind woven synthetic, moisture barrier backings and attached polyurethane cushions available. Contact mill for details.
- WARRANTIES** - 10-Year Wear Warranty
10-Year Delamination Warranty
10-Year Edge Ravel Warranty

CRI Green Label Plus Indoor Air Quality Testing Program - Passes – Certification No. GLP 4078

NOTES:

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step® walk-off tiles or walk-off mats are recommended at building entryways to reduce soiling.

Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture." Performance is not affected by these variables.

Some visual inconsistencies in the surface appearance of all textile products should be expected, including visible seams. This product requires the row cut seaming technique in order to produce quality seams. Seam sealer must be used.

Carpet should be installed according to manufacturer's carpet installation procedures.

*S.E.P. Nylon is: Solution dyed/Space dyed Environmentally Positive nylon by Richmond Carpet Company. SEP nylon is produced using environmentally friendly pigments and is recyclable.