

***SPECIFICATIONS**

QUALITY: **C267T CLASSIC** 24" X 24" Carpet Tile – S.O.P. (Special Order Product-500 Sq.Yd. Min.)
C267V CLASSIC 6 Ft. EnviroFlex® Roll Goods-S.O.P. (Special Order Product-500 Sq.Yd. Min.)

COLORS:

2322 Scarlet Clouds	2331 Etching	2339 Courbet Brown
2323 Forest	2332 Still Life	2340 Wilderness
2324 Seascape	2333 Rain Fall	2342 Woodland
2325 Rembrandt	2334 Blue Evening	2343 Alabaster
2326 Garden Shadow	2335 Winter Sky	2345 Renaissance
2327 Thunder Storm	2336 Nature Study	2346 Versailles
2328 Dusk	2337 Landscape	2348 Fresco
2330 Manet Black	2338 Picnic	2349 Michelangelo
		2350 Sunset

CONSTRUCTION - Multi-Level Pattern Loop
YARN - 100% Zeftron Solure® Nylon contains recycled content
Treated with Blue Shield® soil and stain protector.
DYE METHOD - Solution Dyed
PRIMARY BACKING - 100% Synthetic
SECONDARY BACKING - YARN PLY - EnviroFlex® Performance Engineered Backing w/40% Recycled Content
2 Ply
TUFTED YARN WEIGHT - 20 Ounces Per Sq. Yd. (678 g/m²)
TOTAL WEIGHT - 144 Ounces Per Sq. Yd. (4883 g/m²)
AVG.TUFTED PILE HEIGHT - Approximately .102 inch (2.58 mm)
STITCHES PER INCH - 10 (3.94 stitches/cm)
MACHINE GAUGE - 1/12" (4.72 rows/cm)
DENSITY - 7059
TILE SIZE - 24" X 24" (60.96 cm X 60.96 cm)
ROLL WIDTH - 6' (1.83 m)
FLOORING RADIANT PANEL - ASTM E-648 – Class 1
SMOKE DENSITY - NFPA 258 - Passes
TRAFFIC CLASS - Extra Heavy Commercial Class III
DYE LOT SIZE - Up to 20,000 Square Yards
ADHESIVES - BR200 EnviroFlex® Modular Carpet Adhesive

Installation	Monolithic
Wear Warranty	Useful Life
Edge Ravel Guarantee	Useful Life
Delamination Guarantee	Useful Life
Run Resistance Warranty	Useful Life
Stain Removal Guarantee	Useful Life
Static Warranty	Useful Life
Colorfastness to Light	Useful Life
Colorfastness to Atmospheric Contaminants	Useful Life
Recycling Program	Qualifies for Blue Cycle Reclamation Program

CRI Green Label Plus – Indoor Air Quality Testing Program – Passes – Certification No. GLP 9712

NOTES:

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step® walk-off tiles or walk-off mats are recommended at building entryways to reduce soiling.

Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture". Performance is not affected by these variables

Due to the nature of modular patterned textile products, an exact pattern match cannot be guaranteed. Some visual inconsistencies in the surface appearance of all textile products should be expected, including visible seams.

Carpet should be installed according to manufacturer's carpet installation procedures.