Blue Ridge Commercial Carpet P.O. Box 507, Ellijay, GA 30540
800 354 8951, 706 276 2005, www.blueridgecarpet.com

SPECIFICATIONS

QUALITY:	**C200T CLEAN STEP - STRIPE**	24" x 24" Carpet Tile
	C200V CLEAN STEP - STRIPE	6 Ft. EnviroFlex® Vinyl
	C210T CLEAN STEP - TEXTURE	24" x 24" Carpet Tile
	C210V CLEAN STEP - TEXTURE	6 Ft. EnviroFlex® Vinyl

COLORS: 2258 Charcoal
2259 Slate
2260 Brown

CONSTRUCTION	-	Tufted, Multi Level Loop
YARN	-	100% High Abrasive Nylon
YARN WEIGHT	-	36 Oz. (1221 g/m²)
DYE METHOD	-	Solution Dyed
TOTAL WEIGHT	-	160 Ounces Per Sq.Yd. (5426 g/m²)
SECONDARY BACKING	-	Enviroflex® (Fiberglass Reinforced Vinyl) w/40% Recycled Content
SIZE	-	24" x 24" (60.96 cm x 60.96 cm)
OPTIONS	-	6 Ft. EnviroFlex® Roll Goods Available. Not recommended for multi-breadth installations.
FLOORING RADIANT PANEL	-	ASTM E-648 – Class 1
SMOKE DENSITY	-	NFPA 258 - Passes
ADHESIVE	-	BR200 EnviroFlex® Modular Carpet Adhesive

Installation	-	¼ Turn
Wear Warranty	-	Useful Life
Delamination Guarantee	-	Useful Life
Edge Ravel Guarantee	-	Useful Life
Run Resistance Warranty	-	Useful Life
Static Warranty	-	Useful Life
Colorfastness to Light	-	Useful Life
Colorfastness to Atmospheric Contaminants	-	Useful Life
Recycling Program	-	Qualifies for Blueridge Blue Cycle Reclamation Program

FEATURES:

Performance Construction	– Engineered for heavy foot traffic. No zippering or edge ravel.
High-Low Texture	– Traps dirt, dust and debris. Reduces slips and falls.
UV Stabilized	– Excellent for entryways with strong sunlight.
Large Scraper Yarns	– Provides aggressive scraping action to remove soil from shoe.
Cost Savings	– Helps protect your flooring investment and control maintenance cost.

CRI Green Label Plus Indoor Air Quality Testing Program – Passes – Certification No. GLP 9712

NOTES:
Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step® walk-off tiles or walk-off mats are recommended at building entryways to reduce soiling.

Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture". Performance is not affected by these variables

Due to the nature of patterned textile products, an exact pattern match cannot be guaranteed. Some visual inconsistencies in the surface appearance of all textile products should be expected, including visible seams.

Carpet should be installed according to manufacturer's carpet installation procedures.

Manufactured in U.S.A.