

SPECIFICATIONS

QUALITY: **C299T COMPOSITION** 24" X 24" Carpet Tile (Special Order Product-500 Sq.Yd.Min.)

COLORS:	2551 Template	2555 Ingento
	2552 Caliper	2556 Divider
	2553 Vellum	2557 Compass
	2554 Ruler	2558 Lead

CONSTRUCTION	-	Multi-Level Pattern Loop
YARN	-	100% Zeftron® Solure enviro6ix® Nylon contains a minimum of 25% post industrial and/or post consumer recycled content. Treated with Blue Shield® soil and stain protector.
DYE METHOD	-	Solution Dyed
PRIMARY BACKING	-	100% Synthetic
SECONDARY BACKING	-	EnviroFlex® Performance Engineered Backing w/40% Recycled Content
YARN PLY	-	2 Ply
TUFTED YARN WEIGHT	-	22 Ounces Per Sq. Yd. (746 g/m ²)
TOTAL WEIGHT	-	145 Ounces Per Sq. Yd. (4916 g/m ²)
FINISHED PILE THICKNESS	-	.079 inch approx. (2.01 mm)
STITCHES PER INCH	-	10 (3.94 stitches/cm)
MACHINE GAUGE	-	1/16" (6.30 rows/cm)
DENSITY	-	9750
TILE SIZE	-	24" X 24" (60.96 cm X 60.96 cm)
TRAFFIC CLASS	-	Extra Heavy Commercial Class III
DYE LOT SIZE	-	20,000 Square Yards
ADHESIVE	-	BR200 EnviroFlex® Modular Carpet Adhesive

Installation	-	Checkerboard with Structure and/or Elements; ¼ Turn; Or Brick at Customer Discretion
Wear Warranty	-	Useful Life
Edge Ravel Guarantee	-	Useful Life
Delamination Guarantee	-	Useful Life
Run Resistance Warranty	-	Useful Life
Stain Removal Guarantee	-	Useful Life
Static Warranty	-	Useful Life
Colorfastness to Light	-	Useful Life
Colorfastness to Atmospheric Contaminants	-	Useful Life
Recycling Program	-	Qualifies for Blueridge Blue Cycle Reclamation Program

CRI Green Label Plus Indoor Air Quality Testing Program – Passes – Certification No. GLP 9712

NOTES:

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step® walk-off tiles or walk-off mats are recommended at building entryways to reduce soiling.

Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture". Performance is not affected by these variables

Due to the nature of modular patterned textile products, an exact pattern match cannot be guaranteed. Some visual inconsistencies in the surface appearance of all textile products should be expected, including visible seams.

Carpet should be installed according to manufacturer's carpet installation procedures.