

**QUALITY: 2300 CONEY ISLAND**

<b>COLORS:</b>	2301 Midnight	2305 Haven	2309 Bushel
	2302 Quarry	2306 Gleneden	2310 Taupette
	2303 Lagoon	2307 Cornflower	2311 Greyridge
	2304Titanic	2308 Copperhead	2312 Plumoss

<b>CONSTRUCTION</b>	-	Tufted Multi Level Loop
<b>YARN</b>	-	83% SEP* Solution Dyed Continuous Filament Nylon 17% Yarn Dyed Nylon
<b>TUFTED YARN WEIGHT</b>	-	26 Ounces (881g/m <sup>2</sup> )
<b>MACHINE GAUGE</b>	-	1/10" (3.94 rows/cm)
<b>STITCHES PER INCH</b>	-	8 (3.15 stitches/cm)
<b>AVERAGE PILE HEIGHT</b>	-	.130 (3.30 mm)
<b>DYE METHOD</b>	-	83% Solution Dyed, 17% Yarn Dyed
<b>SOIL / STAIN PROTECTION</b>	-	Blue Shield® Soil and Stain Protector
<b>DENSITY FACTOR</b>	-	7,200
<b>PRIMARY BACK</b>	-	Woven Polypropylene
<b>SECONDARY BACK</b>	-	Woven Synthetic
<b>RADIANT PANEL TEST</b>	-	Class I
<b>NBS SMOKE CHAMBER TEST</b>	-	Passes
<b>STATIC</b>	-	Less than 3.5 kv
<b>PATTERN REPEAT</b>	-	½" W X 1" L (1.27 cm W X 2.54 cm L)
<b>COORDINATING STYLES</b>	-	The Americana Series
<b>OPTIONAL BACKINGS</b>	-	High tuft-bind woven synthetic, moisture barrier backings and attached polyurethane cushions available. Contact mill for details.
<b>WARRANTIES</b>	-	10-Year Wear Warranty 10-Year Delamination Warranty 10-Year Edge Ravel Warranty

**CRI Green Label Plus Indoor Air Quality Testing Program** - Passes – Certification No. GLP 4078

**NOTES:**

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step® walk-off tiles or walk-off mats are recommended at building entryways to reduce soiling.

Specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber, temperature, and humidity, and may vary within normal industry tolerances. Performance is not affected by such variables.

Due to the nature of patterned textile products, an exact pattern match cannot be guaranteed. Some visual inconsistencies in the surface appearance of all textile products should be expected, including visible seams. This product requires the row cut seaming technique in order to produce quality seams. Seam sealer must be used.

Carpet should be installed according to manufacturer's carpet installation procedures.

\*S.E.P. Nylon is: Solution dyed Environmentally Positive nylon by Richmond Carpet Company. SEP nylon is produced using environmentally friendly pigments and is recyclable.