

SPECIFICATIONS

QUALITY: 2300 CONEY ISLAND

COLORS:	2301 Midnight	2305 Haven	2309 Bushel
	2302 Quarry	2306 Gleneden	2310 Taupette
	2303 Lagoon	2307 Cornflower	2311 Greyridge
	2304Titanic	2308 Copperhead	2312 Plumoss

- CONSTRUCTION** - Tufted Multi Level Loop
- YARN** - 100% SEP* Nylon with Antistat
- TUFTED YARN WEIGHT** - 26 Ounces (881g/m²)
- MACHINE GAUGE** - 1/10" (3.94 rows/cm)
- STITCHES PER INCH** - 8 (3.15 stitches/cm)
- AVERAGE PILE HEIGHT** - .130 (3.30 mm)
- DYE METHOD** - 83% Solution Dyed / 17% Space Dyed
- SOIL / STAIN PROTECTION** - Blue Shield® Soil and Stain Protector
- DENSITY FACTOR** - 7,200
- PRIMARY BACK** - Woven Polypropylene
- SECONDARY BACK** - Woven Synthetic
- RADIANT PANEL TEST** - Class I
- NBS SMOKE CHAMBER TEST** - Passes
- PATTERN REPEAT** - ½" W X 1" L (1.27 cm W X 2.54 cm L)
- COORDINATING STYLES** - The Americana Series
- RECYCLING PROGRAM** - Qualifies for Blueridge Blue Cycle Reclamation Program
- OPTIONAL BACKINGS** - High tuft-bind woven synthetic, moisture barrier backings and attached polyurethane cushions available. Contact mill for details.
- WARRANTIES** - 10-Year Wear Warranty
10-Year Delamination Warranty
10-Year Edge Ravel Warranty

CRI Green Label Plus Indoor Air Quality Testing Program - Passes – Certification No. GLP 4078

NOTES:

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step® walk-off tiles or walk-off mats are recommended at building entryways to reduce soiling.

Specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber, temperature, and humidity, and may vary within normal industry tolerances. Performance is not affected by such variables.

Due to the nature of patterned textile products, an exact pattern match cannot be guaranteed. Some visual inconsistencies in the surface appearance of all textile products should be expected, including visible seams. This product requires the row cut seaming technique in order to produce quality seams. Seam sealer must be used.

Carpet should be installed according to manufacturer's carpet installation procedures.

*S.E.P. Nylon is: Solution dyed/Space dyed Environmentally Positive nylon by Richmond Carpet Company. SEP nylon is produced using environmentally friendly pigments and is recyclable.