

SPECIFICATIONS

QUALITY:	C231T CONFETTI	24" X 24" Carpet Tile	
	C231V CONFETTI	6 Ft. EnviroFlex®	
COLORS:	2849 Symmetrical Taupe	2852 Golden Light	2855 Charcoal Fractions
	2850 Red Glass	2853 Brown Reflections	2856 Prism Blue
	2851 Chocolate Fragments	2854 Mirror Gray	2857 Green Delight

CONSTRUCTION	-	Multi-Level Pattern Loop
YARN	-	100% Antron Lumena® Solution Dyed Nylon with Dura Tech® Soil Resistant Treatment and Recycled Content
DYE METHOD	-	Solution Dyed
PRIMARY BACKING	-	100% Synthetic
SECONDARY BACKING	-	EnviroFlex® Performance Engineered Backing w/40% Recycled Content
TUFTED YARN WEIGHT	-	20 Ounces Per Sq. Yd. (678 g/m²)
TOTAL WEIGHT	-	Approximately 144 Ounces Per Sq. Yd. (4882 g/m²)
FINISHED PILE THICKNESS	-	Approximately .110 inch (2.79 mm)
STITCHES PER INCH	-	10 (3.94 stitches/cm)
MACHINE GAUGE	-	1/12" (4.72 rows/cm)
DENSITY FACTOR	-	6545
TILE SIZE	-	24" X 24" (60.96 cm X 60.96 cm)
ROLL WIDTH	-	6 Ft. (1.83 cm)
CRI TRAFFIC RATING	-	Severe
PATTERN REPEAT	-	½" W (1.28 cm W)
ADHESIVE	-	BR200 EnviroFlex® Modular Carpet Adhesive

Installation	-	¼ Turn
Wear Warranty	-	Useful Life
Edge Ravel Guarantee	-	Useful Life
Delamination Guarantee	-	Useful Life
Run Resistance Warranty	-	Useful Life
Stain Removal Guarantee	-	Useful Life
Static Warranty	-	Useful Life
Colorfastness to Light	-	10 Year
Colorfastness to Atmospheric Contaminants	-	5 Year
Recycling Program	-	Qualifies for Blueridge Blue Cycle Reclamation Program

CRI Green Label Plus Indoor Air Quality Testing Program – Passes – Certification No. GLP 9712

NOTES:

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step® Walk-Off Tiles or walk-off mats are recommended at building entryways to reduce soiling.

Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture". Performance is not affected by these variables

Due to the nature of modular patterned textile products, an exact pattern match cannot be guaranteed. Some visual inconsistencies in the surface appearance of all textile products should be expected, including visible seams.

Carpet should be installed according to manufacturer's carpet installation procedures.