

Effective Date: June 14, 2007

**\*SPECIFICATIONS**

**QUALITY: 5700 CONNECTOR - Quick Ship**

<b>COLORS:</b>	5701 Oatmeal	5704 Aloe
	5702 Midnight	5705 Graphite
	5703 Raisin	5706 Blue Haze

<b>CONSTRUCTION</b>	-	Tufted Multi-Level Loop
<b>YARN</b>	-	100% SEP* Solution Dyed Continuous Filament Nylon with Antistat
<b>TUFTED YARN WEIGHT</b>	-	24 Ounces (814g/m <sup>2</sup> )
<b>MACHINE GAUGE</b>	-	1/10" (3.94 rows/cm)
<b>STITCHES PER INCH</b>	-	10.5 (4.13 stitches/cm)
<b>FINISHED PILE THICKNESS</b>	-	.151 (3.83 mm)
<b>WIDTH</b>	-	12 ft. (3.66 m)
<b>DYE METHOD</b>	-	100% Solution Dyed
<b>SOIL / STAIN PROTECTION</b>	-	Blue Shield® Soil and Stain Protector
<b>DENSITY</b>	-	5722
<b>PRIMARY BACKING</b>	-	Woven Polypropylene
<b>SECONDARY BACKING</b>	-	Woven Synthetic
<b>RADIANT PANEL TEST</b>	-	Class I
<b>NBS SMOKE CHAMBER TEST</b>	-	Passes
<b>PATTERN REPEAT</b>	-	½" W x 1 ½" L (1.27 cm x 3.81 cm)
<b>AVERAGE DELIVERY</b>	-	Two Weeks**
<b>OPTIONAL BACKINGS</b>	-	High tuft-bind woven synthetic, moisture barrier backings and attached polyurethane cushions available Contact mill for details.
<b>WARRANTIES</b>	-	10-Year Wear Warranty 10-Year Delamination Warranty 10-Year Edge Ravel Warranty

**CRI Green Label Plus Indoor Air Quality Testing Program - Passes – Certification No. 4078**

**NOTES:**

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step® walk-off tiles or walk-off mats are recommended at building entryways to reduce soiling.

Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture." Performance is not affected by these variables.

Some visual inconsistencies in the surface appearance of all textile products should be expected, including visible seams. This product requires the row cut seaming technique in order to produce quality seams. Seam sealer must be used.

Carpet should be installed according to manufacturer's carpet installation procedures.

\*S.E.P. Nylon is: Solution dyed Environmentally Positive nylon by Richmond Carpet Company. SEP nylon is produced using environmentally friendly pigments and is recyclable.

\*\*Ten working days from date of credit approval.