

Effective Date: September 17, 2003

*SPECIFICATIONS

QUALITY: C-274 CRESTVIEW

COLORS:

9873 Peat	9887 Old Glory	9901 Deep Amethyst	9884 Chambray
9876 Smoked Cloud	9886 Mustard Seed	9911 Brickware	9907 Sepia
9872 Granite Stone	9882 Farmland	9908 Nutmeg Spice	9895 Purple Sky
9885 Hunting Green	9918 Dried Straw	9896 Windsor Blue	9917 Gern
9874 Forest Moss	9919 Goldenrod	9870 Charcoal Mist	9910 Clay Pot
9875 Dark Sage	9879 Bark Chip	9899 Cerulean Blue	9897 Duck Egg
9892 Rollinghill	9881 Sandgrain	9905 Dark Mushroom	9871 Nightstar
9883 Lichen	9880 Beeswax	9916 Wild Chestnut	9906 Cranapple
9878 Seaweed	9912 Woodstick	9898 Mountain Spring	9902 Wineberry

PILE FIBER	-	100% Antron Legacy Nylon with Dura Tech Soil Resistance Treatment.
YARN PLY	-	2 Ply
TUFTED YARN WEIGHT	-	38 Ounces per sq. yd. (1288 g/m ²)
MACHINE GAUGE	-	1/8" (3.15 rows/cm)
STITCHES PER INCH	-	12 (4.72 stitches/cm)
FINISHED PILE THICKNESS	-	.233 Inch Approx. (5.91 mm)
DENSITY FACTOR	-	5,871
WIDTH	-	12' (3.66m)
PRIMARY BACKING	-	100% Synthetic
SECONDARY BACKING	-	Power Lock® High Performance Backing
ASTM E-648	-	Average Critical Radiant Flux: Greater than .45 - Class 1
NBS SMOKE CHAMBER TEST	-	Specific Optical Density: Less than 450
COORDINATE PRODUCTS	-	Heirloom Series

WARRANTIES:

Wear Warranty	-	10 Year
Static Warranty	-	Useful Life
Edge Ravel Guarantee	-	Useful Life
Delamination Guarantee	-	Useful Life
Run Resistance Guarantee	-	Useful Life
Recycling Program	-	Qualifies for Invista Reclamation® Program

CRI – INDOOR AIR QUALITY TESTING PROGRAM - PASSES - CERTIFICATION NO. 14222818

NOTES:

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step® walk-off tiles by Blue Ridge or walk-off mats are recommended at building entryways to reduce soiling.

*Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber, fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture". Performance is not affected by these variables

As with all patterned carpet, a perfect pattern match may not be possible due to the fact that carpet is a textile subject to shrinking and expansion in both length and width. A plus or minus 1% should be expected. However, a reasonable pattern match may be achieved by competent installers using power stretching and stay nailing techniques.

Installation of pattern carpet requires more time to install correctly, which should be considered in the original installation quotation.