

Effective Date: August 12, 2003

\*SPECIFICATIONS

QUALITY: D-990 DUKES CREEK

COLORS (13):	2404 Catch and Release	2408 Angler	2412 Reel
	2416 Smithgall	2405 Pebble	2409 Waders
	2413 Tackle Box	2406 Lure	2410 Fly Fishing
	2414 Trout Stream	2407 Browns	2411 Mountain Laurel
	2415 Watershed		

CONSTRUCTION	-	Multi-Level Pattern Loop
YARN	-	100% Zeftron Solure Nylon, contains recycled content. Treated with a stain protector and soil repellent.
DYE METHOD	-	Solution Dyed
PRIMARY BACKING	-	100% Synthetic
YARN PLY	-	2 Ply
TUFTED YARN WEIGHT	-	26 ozs. per sq. yd. (882 g/m <sup>2</sup> )
FINISHED PILE THICKNESS	-	Approximately .110 inch (2.79 mm)
STITCHES PER INCH	-	14 (5.51 stitches/cm)
MACHINE GAUGE	-	1/10" (3.94 rows/cm)
DENSITY	-	8,509
WIDTH	-	12' (3.66m)
TRAFFIC CLASS	-	Extra Heavy Commercial Class III
FLOORING RADIANT PANEL	-	ASTM E-648 – Class I
SMOKE DENSITY	-	NFPA 258 - Passes
SECONDARY BACKING	-	Power Lock® High Performance Backing
DYE LOT SIZE	-	Up to 20,000 Square Yards
LIGHT FASTNESS	-	4 or Better After 8 Cycles of Exposure – AATCC 16
OZONE	-	4 or Better After 8 Cycles of Exposure – AATCC 129
OXIDES OF NITROGEN	-	4 or Better After 8 Cycles of Exposure – AATCC 164

WARRANTIES:

Wear Warranty	-	Useful Life
Edge Ravel Guarantee	-	Useful Life
Delamination Guarantee	-	Useful Life
Run Resistance Warranty	-	Useful Life
Stain Removal Guarantee	-	Useful Life
Static Warranty	-	Useful Life
Colorfastness to Light	-	Useful Life
Colorfastness to Atmospheric Contaminants	-	Useful Life
Recycling Program	-	Qualifies for 6ix Again® Program

CRI – INDOOR AIR QUALITY TESTING PROGRAM – PASSES – CERTIFICATION NO. 16654078

NOTES:

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step® Walk-off tiles by Blue Ridge are recommended at building entryways to reduce soiling.

Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture". Performance is not affected by these variables

Due to the nature of modular patterned textile products, an exact pattern match cannot be guaranteed. Some visual inconsistencies in the surface appearance of all textile products should be expected, including visible seams.

Carpet should be installed according to manufacturer's carpet installation procedures.