Blue Ridge Commercial Carpet P.O. Box 507, Ellijay, GA 30540
800 354 8951, 706 276 2005, www.blueridgecarpet.com

SPECIFICATIONS

QUALITY: **E300T ELEMENTS** 24" X 24" Carpet Tile (Special Order Product 500 Sq.Yd.Min.)
E300V ELEMENTS 6 Ft. EnviroFlex® (Special Order Product 500 Sq.Yd.Min.)

COLORS:

2559 Template	2563 Ingento
2560 Caliper	2564 Divider
2561 Vellum	2565 Compass
2562 Ruler	2566 Lead

CONSTRUCTION	-	Multi-Level Pattern Loop
YARN	-	100% Zeftron® Solure enviro6ix®Nylon contains a minimum of 25% post industrial and/or post consumer recycled content. Treated with Blue Shield® soil and stain protector.
DYE METHOD	-	Solution Dyed
PRIMARY BACKING	-	100% Synthetic
SECONDARY BACKING	-	EnviroFlex® Performance Engineered Backing w/40% Recycled Content
YARN PLY	-	2 Ply
TUFTED YARN WEIGHT	-	18 Ounces Per Sq. Yd. (610 g/m²)
TOTAL WEIGHT	-	141 Ounces Per Sq. Yd. Approx. (4781 g/m²)
FINISHED PILE THICKNESS	-	.090 inch approx. (2.29 mm)
STITCHES PER INCH	-	10 (3.94 stitches/cm)
MACHINE GAUGE	-	1/12" (4.72 rows/cm)
DENSITY	-	7200
TILE SIZE	-	24" X 24" (60.96 cm X 60.96 cm)
ROLL WIDTH	-	6 Ft. (1.83 cm)
PATTERN REPEAT	-	
TRAFFIC CLASS	-	Extra Heavy Commercial Class III
ADHESIVE	-	BR200 EnviroFlex® Modular Carpet Adhesive

Installation	-	Checkerboard with Structure and/or Composition; ¼ Turn; or Brick at Customer Discretion
Wear Warranty	-	Useful Life
Edge Ravel Guarantee	-	Useful Life
Delamination Guarantee	-	Useful Life
Run Resistance Warranty	-	Useful Life
Stain Removal Guarantee	-	Useful Life
Static Warranty	-	Useful Life
Colorfastness to Light	-	Useful Life
Colorfastness to Atmospheric Contaminants	-	Useful Life
Recycling Program	-	Qualifies for Blueridge Blue Cycle Reclamation Program

CRI Green Label Plus Indoor Air Quality Testing Program – Passes – Certification No. GLP 9712

NOTES:

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step® walk-off tiles or walk-off mats are recommended at building entryways to reduce soiling.

Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture". Performance is not affected by these variables

Due to the nature of modular patterned textile products, an exact pattern match cannot be guaranteed. Some visual inconsistencies in the surface appearance of all textile products should be expected, including visible seams.

Carpet should be installed according to manufacturer's carpet installation procedures.