

Effective Date: May 7, 2003

*SPECIFICATIONS

QUALITY: F-100T FAIR ISLE 24" x 24" Carpet Tile

| | | | |
|---------|------------------|------------------------|-------------------|
| COLORS: | 2360 Snow Tweed | 2364 Cardigan Rust | 2368 Sweater Gray |
| | 2361 Knit Purl | 2365 Chocolate Heather | 2369 Pasture |
| | 2362 Mitten Gold | 2366 Baltic Green | 2370 Island |
| | 2363 Shetland | 2367 Fog | 2371 North Sea |

| | | |
|-------------------------|---|---|
| CONSTRUCTION | - | Multi-Level Pattern Loop |
| YARN | - | 100% Zeftron® Solure contains recycled content. Treated with a stain protector and soil repellent. |
| DYE METHOD | - | Solution Dyed |
| PRIMARY BACKING | - | 100% Synthetic |
| YARN PLY | - | 2 Ply |
| TUFTED YARN WEIGHT | - | 20 oz. per sq. yd. (678 g/m ²) |
| TOTAL WEIGHT | - | 144 oz. per sq. yd. (4883 g/m ²) |
| FINISHED PILE THICKNESS | - | Approximately .120 inch (3.10mm) |
| STITCHES PER INCH | - | 10 (3.94 stitches/cm) |
| MACHINE GAUGE | - | 1/12" (4.72 rows/cm) |
| DENSITY | - | 6,000 |
| SIZE | - | 24" x 24" (60.96cm x 60.96cm) |
| TRAFFIC CLASS | - | Extra Heavy Commercial Class III |
| SECONDARY BACKING | - | EnviroFlex® Performance Engineered Backing with recycled content |
| DYE LOT SIZE | - | Up to 20,000 square yards |
| ADHESIVE | - | CA02V Vinyl Carpet Adhesive JS02V Vinyl Carpet Seam Sealer JE02V Vinyl Carpet Seam Sealer |

WARRANTIES:

| | | |
|---|---|----------------------------------|
| Installation | - | Monolithic |
| Wear Warranty | - | Useful Life |
| Edge Ravel Guarantee | - | Useful Life |
| Delamination Guarantee | - | Useful Life |
| Run Resistance Warranty | - | Useful Life |
| Stain Removal Guarantee | - | Useful Life |
| Static Warranty | - | Useful Life |
| Colorfastness to Light | - | Useful Life |
| Colorfastness to Atmospheric Contaminants | - | Useful Life |
| Recycling Program | - | Qualifies for Gix Again® Program |

CRI INDOOR AIR QUALITY CERTIFICATION NO. – 34679712

NOTES:

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Walk-off mats or Clean Step® Walk-off tiles from Blue Ridge are recommended at building entryways to reduce soiling.

Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture". Performance is not affected by these variables.

Due to the nature of modular patterned textile products, an exact pattern match cannot be guaranteed. Some visual inconsistencies in the surface appearance of all textile products should be expected, including visible seams.

Carpet should be installed according to manufacturer's carpet installation procedures.