

Effective Date: September 17, 2003

SPECIFICATIONS

QUALITY:	F-150 FALLING LEAVES	
COLORS:	2417 Maple Leaf	2421 Mountain Top
	2418 Autumn	2422 Early Frost
	2419 Camp Fire	2423 Hiking Trail
	2420 Country Road	2424 October
CONSTRUCTION	-	Textured Pattern Loop
YARN	-	100% Zeftron Solure Nylon contains recycled content. Treated with a stain protector and a soil repellent.
DYE METHOD	-	Solution Dyed
PRIMARY BACKING	-	100% Synthetic
YARN PLY	-	2 Ply
TUFTED YARN WEIGHT	-	26 ozs. per sq. yd. (882 g/m <sup>2</sup> )
FINISHED PILE THICKNESS	-	Approximately .130 inch (3.30 mm)
STITCHES PER INCH	-	12 (4.72 stitches/cm)
MACHINE GAUGE	-	1/12" (4.72 rows/cm)
DENSITY	-	7,200
WIDTH	-	12' (3.66m)
TRAFFIC CLASS	-	Extra Heavy Commercial III
FLOORING RADIANT PANEL	-	ASTM E-648 – Class 1
SMOKE DENSITY	-	NFPA 258 – Passes
SECONDARY BACKING	-	Power Lock® High Performance Backing
DYE LOT SIZE	-	Up to 20,000 sSquare yards
PATTERN REPEAT	-	24" W x 29" L (60.96 cm W x 73.66 cm L)
COORDINATE PRODUCT	-	Dukes Creek

Wear Warranty	-	Useful Life
Edge Ravel Guarantee	-	Useful Life
Delamination Guarantee	-	Useful Life
Run Resistance Warranty	-	Useful Life
Stain Removal Guarantee	-	Useful Life
Static Warranty	-	Useful Life
Colorfastness to Light	-	Useful Life
Colorfastness to Atmospheric Contaminants	-	Useful Life
Recycling Program	-	Qualifies for 6ix™ Again Program

CRI – Indoor Air Quality Testing Program – Passes – Certification No. 16654078

NOTES:

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step® walk-off tiles by Blue Ridge or walk-off mats are recommended at building entryways to reduce soiling.

Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture". Performance is not affected by these variables.

Due to the nature of patterned textile products, an exact pattern match cannot be guaranteed. Some visual inconsistencies in the surface appearance of all textile products should be expected, including visible seams. This product (Falling Leaves) requires the row cut seaming technique in order to produce quality seams. Seam sealer must be used.

Carpet should be installed according to manufacturer's carpet installation procedures.