

Effective Date: September 17, 2003

*SPECIFICATIONS

QUALITY: F-210 FIELD

COLORS:	2070 Sand Lot	2073 Barley	2076 Winewood
	2071 Green Drift	2074 Cordova	2077 Titan Blue
	2072 Bluegrass	2075 Barnstone	2078 Thicket

CONSTRUCTION	-	Textured Pattern Loop
YARN	-	100% Zeftron® Solure Nylon contains recycled content. Treated with a stain protector and soil repellent.
DYE METHOD	-	Solution Dyed
PRIMARY BACKING	-	100% Synthetic
YARN PLY	-	3 Ply
TUFTED YARN WEIGHT	-	28 Ounces Per Sq. Yd. (949 g/m ²)
FINISHED PILE THICKNESS	-	Approximately .118 inch (3.0 mm)
STITCHES PER INCH	-	10 (3.94 stitches/cm)
MACHINE GAUGE	-	1/12" (4.72 rows/cm)
DENSITY FACTOR	-	8,542
WIDTH	-	12' (3.66m)
TRAFFIC CLASS	-	Extra Heavy Commercial III
FLOORING RADIANT PANEL	-	ASTM E-648 – Class 1
SMOKE DENSITY	-	NFPA 258 – Passes
COORDINATE PRODUCT(S)	-	Mirada VI
SECONDARY BACKING	-	Power Lock® High Performance Backing
DYE LOT SIZE	-	Up to 20,000 Square Yards
PATTERN REPEAT	-	24" W x 13" L (60.96 cm W x 33.02 cm L)

WARRANTIES:

Wear Warranty	-	Useful Life
Edge Ravel Guarantee	-	Useful Life
Delamination Guarantee	-	Useful Life
Stain Removal Guarantee	-	Useful Life
Static Warranty	-	Useful Life
Colorfastness to Light	-	Useful Life
Colorfastness to Atmospheric Contaminants	-	Useful Life
Recycling Program	-	Qualifies for 6ix Again® Program

CRI – Indoor Air Quality Testing Program – Passes – Certification No. 16654078

NOTES:

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step® walk-off tiles by Blue Ridge or walk-off mats are recommended at building entryways to reduce soiling.

Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture". Performance is not affected by these variables

Due to the nature of patterned textile products, an exact pattern match cannot be guaranteed. Some visual inconsistencies in the surface appearance of all textile products should be expected, including visible seams. This product (Field) requires the row cut seaming technique in order to produce quality seams. Seam sealer must be used.

Carpet should be installed according to manufacturer's carpet installation procedures.