

Date: September 17, 2003

*SPECIFICATIONS

QUALITY: F-220 FINE LINE

COLORS:	2142 Oyster	2146 Mist	2150 Lavender	2154 Olive
	2143 Cashmere	2147 Celadon	2151 Thistle	2155 Loden
	2144 Taupe	2148 Algae	2152 Eggplant	2156 Walnut
	2145 Dune	2149 Laurel	2153 Raisin	2157 Java

CONSTRUCTION	-	Multi-Level Pattern Loop
PILE FIBER	-	100% Antron Legacy Nylon with Dura Tech Soil Resistance Treatment.
YARN PLY	-	2 Ply
TUFTED YARN WEIGHT	-	28 ozs. per sq. yd. (949 g/m ²)
MACHINE GAUGE	-	1/10" (3.94 rows/cm)
STITCHES PER INCH	-	13 (5.12 stitches/cm)
FINISHED PILE THICKNESS	-	.158 inch approx. (4.01 mm)
DENSITY FACTOR	-	6,379
WIDTH	-	12' (3.66m)
PRIMARY BACKING	-	100% Synthetic
SECONDARY BACKING	-	Power Lock® High Performance Backing
ASTM E-648	-	Average Critical Radiant Flux: Greater than .45 - Class 1
NBS SMOKE CHAMBER TEST	-	Specific Optical Density: Less than 450
COORDINATE PRODUCTS	-	Foundation

WARRANTIES:

Wear Warranty	-	10 Year
Static Warranty	-	Useful Life
Delamination Guarantee	-	Useful Life
Edge Ravel Guarantee	-	Useful Life
Run Resistance Warranty	-	Useful Life
Recycling Program	-	Qualifies for the Invista Reclamation Program

CRI INDOOR AIR QUALITY TESTING PROGRAM – PASSES – CERTIFICATION NO. 14222878

NOTES:

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step® walk-off tiles by Blue Ridge or walk-off mats are recommended at building entryways to reduce soiling.

*Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber, fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture". Performance is not affected by these variables.

As with all patterned carpet, a perfect pattern match may not be possible due to the fact that carpet is a textile subject to shrinking and expansion in both length and width. A plus or minus 1% should be expected. However, a reasonable pattern match may be achieved by competent installers using power stretching and stay nailing techniques.

Installation of pattern carpet requires more time to install correctly, which should be considered in the original installation quotation.