

Effective Date: September 17, 2003

\*SPECIFICATIONS

QUALITY: G-250 GARDEN

|         |                  |                |                 |
|---------|------------------|----------------|-----------------|
| COLORS: | 2070 Sand Lot    | 2073 Barley    | 2076 Winewood   |
|         | 2071 Green Drift | 2074 Cordova   | 2077 Titan Blue |
|         | 2072 Bluegrass   | 2075 Barnstone | 2078 Thicket    |

|                         |   |  |
|-------------------------|---|--|
| CONSTRUCTION            | - | Textured Pattern Loop  |
| YARN                    | - | 100% Zeftron® Solure Nylon contains recycled content. Treated with a stain protector and soil repellent. |
| DYE METHOD              | - | Solution Dyed  |
| PRIMARY BACKING         | - | 100% Synthetic   |
| YARN PLY                | - | 3 Ply  |
| TUFTED YARN WEIGHT      | - | 28 ozs. per sq. yd. (949 g/m <sup>2</sup> )  |
| FINISHED PILE THICKNESS | - | Approximately .112 inch (2.84 mm)  |
| STITCHES PER INCH       | - | 10 (3.94 stitches/cm)  |
| MACHINE GAUGE           | - | 1/12" (4.72 rows/cm)   |
| DENSITY FACTOR          | - | 9,000  |
| WIDTH                   | - | 12' (3.66m)  |
| TRAFFIC CLASS           | - | Extra Heavy Commercial III   |
| FLOORING RADIANT PANEL  | - | ASTM E-648 – Class 1   |
| SMOKE DENSITY           | - | NFPA 258 – Passes  |
| COORDINATE PRODUCT(S)   | - | Mirada VI  |
| SECONDARY BACKING       | - | PowerLock® High Performance Backing  |
| DYE LOT SIZE            | - | Up to 20,000 square yards  |
| PATTERN REPEAT          | - | 24" W x 36" L (60.96 cm W x 91.44 cm L)  |

WARRANTIES:

|   |   |                                  |
|---|---|----------------------------------|
| Edge Ravel Guarantee                      | - | Useful Life                      |
| Delamination Guarantee                    | - | Useful Life                      |
| Wear Warranty                             | - | Useful Life                      |
| Stain Removal Guarantee                   | - | Useful Life                      |
| Static Warranty                           | - | Useful Life                      |
| Colorfastness to Light                    | - | Useful Life                      |
| Colorfastness to Atmospheric Contaminants | - | Useful Life                      |
| Recycling Program                         | - | Qualifies for 6ix Again® Program |

CRI – Indoor Air Quality Testing Program – Passes – Certification No. 16654078

NOTES:

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step® walk-off tiles by Blue Ridge or walk-off mats are recommended at building entryways to reduce soiling.

Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture". Performance is not affected by these variables.

Due to the nature of patterned textile products, an exact pattern match cannot be guaranteed. Some visual inconsistencies in the surface appearance of all textile products should be expected, including visible seams. This product (Garden) requires the row cut seaming technique in order to produce quality seams. Seam sealer must be used.

Carpet should be installed according to manufacturer's carpet installation procedures.