

Effective Date: January 18, 2006

*SPECIFICATIONS

QUALITY: G-750 GOLDEN AGE

COLORS:	2716 Valentino	2722 Stock Market	2728 Daisy	2734 East Egg
	2717 Automobile	2723 Fitzgerald	2729 Bootleg	2735 Suburbs
	2718 Rolls	2724 Nightclub	2730 Gold Rush	2736 Green Light
	2719 Prohibition	2725 Einstein	2731 Radio	2737 American Dream
	2720 Movies	2726 Electricity	2732 C. Chaplin	2738 The Blues
	2721 Jazz Band	2727 Technicolor	2733 Cubists	2739 Post-War

CONSTRUCTION	-	Blue Sky® Technology – Tip Sheared
PILE FIBER Treatment.	-	100% Antron Legacy Nylon with Dura Tech Soil Resistance
YARN PLY	-	2 Ply
TUFTED YARN WEIGHT	-	32 ozs. per sq. yd. (1085 g/m ²)
TOTAL WEIGHT	-	69 ozs. Approx.
MACHINE GAUGE	-	1/12" (4.72 rows/cm)
STITCHES PER INCH	-	12 (4.72 stitches/cm)
FINISHED PILE THICKNESS	-	.175 inch approx. (4.45 mm)
DENSITY FACTOR	-	6,583
WIDTH	-	12' (3.66m)
PRIMARY BACKING	-	100% Synthetic
SECONDARY BACKING	-	Power Lock® High Performance Backing
ASTM E-648	-	Average Critical Radiant Flux: Greater than .45 - Class 1
NBS SMOKE CHAMBER TEST	-	Specific Optical Density: Less than 450
COORDINATE PRODUCTS	-	Glamour, Zoot Suit
RECYCLING PROGRAM	-	Qualifies for the Invista Reclamation Program

WARRANTIES:

WEAR WARRANTY	10 Year
STATIC WARRANTY	Useful Life
EDGE RAVEL GUARANTEE	Useful Life
DELAMINATION GUARANTEE	Useful Life

CRI Green Label Plus Indoor Air Quality Testing Program – Passes – Certification No. GLP 2878

NOTES:

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step walk-off tiles by Blue Ridge or walk-off mats are recommended at building entryways to reduce soiling.

*Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber, fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture". Performance is not affected by these variables

Due to the nature of patterned textile products, an exact pattern match cannot be guaranteed. Some visual inconsistencies in the surface appearance of all textile products should be expected, including visible seams. This product, Golden Age, requires the row cut seaming technique in order to produce quality seams. Seam sealer must be used.

Installation of pattern carpet requires more time to install correctly, which should be considered in the original installation quotation. Carpet must be installed according to manufacturer's installation procedures.