

*SPECIFICATIONS

QUALITY: G390 GREAT INSPIRATIONS

COLORS: (76)	2764 Fresco	2783 Cruise	2802 Terra Coral	2821 Demitasse
	2765 Biscotti	2784 Newport	2803 Wisteria	2822 Spiced Tea
	2766 Ginseng	2785 Azurite	2804 Tempest	2823 Black Coffee
	2767 Bistre	2786 Adriatic	2805 Palomino	2824 Haze
	2768 Margarita	2787 Lagoon	2806 Varsity	2825 Whisper
	2769 Delta	2788 Fairway	2807 Diva	2826 Satin
	2770 Cappuccino	2789 Atlantic	2808 Bronco	2827 Wistful
	2771 Taupestone	2790 Regatta	2809 Cameo	2828 Chateau
	2772 Greenhouse	2791 Verdi	2810 Cornsilk	2829 Sand Castle
	2773 Driftwood	2792 Jardin	2811 Rice Wine	2830 Moon Dust
	2774 Indian Spice	2793 Bleu	2812 Just Peachy	2831 Fossil
	2775 Cactus Pine	2794 Berry Good	2813 Twine	2832 Mushroom
	2776 Aw Nuts	2795 Rio Rose	2814 Sand Paper	2833 Sterling
	2777 Bronzing	2796 Jasper	2815 Freestone	2834 Gotham
	2778 Grass Roots	2797 Plum Crazy	2816 Sahara	2835 Mystique
	2779 Oasis	2798 Tuscan	2817 Mango Tango	2836 Ironworks
	2780 Aqueous	2799 Brazen	2818 Sable	2837 Absolute
	2781 Bermuda	2800 Grape Escape	2819 Raffia	2838 Shadow
	2782 Rainforest	2801 Cinnabar	2820 Brandy	2839 Radiant

CONSTRUCTION Blue Sky® Technology – Tip Sheared
PILE FIBER 100% Antron Legacy Nylon with DuraTech® Soil Resistance Treatment.
BENEFITS DuraTech® soil resistant treatment provides superior soil resistance durable for the useful life of the carpet. Antron® Legacy carpet face fiber has a 30% lower Total Environmental Impact than typical industry.

TUFTED YARN WEIGHT 40 Ounces Per Sq. Yd. (1085 g/m²)
TOTAL WEIGHT 77 Oz. Approx.
MACHINE GAUGE 1/8" (3.15 rows/cm)
STITCHES PER INCH 12 (4.72 stitches/cm)
FINISHED PILE THICKNESS .269 Inch Approx. (6.83 mm)
DENSITY FACTOR 5353
CRI TRAFFIC RATING Heavy
WIDTH 12' (3.66m)
PRIMARY BACKING 100% Synthetic
SECONDARY BACKING Power Lock® High Performance Backing
ASTM E-648 Average Critical Radiant Flux: Greater than .45 - Class 1
NBS SMOKE CHAMBER TEST Specific Optical Density: Less than 450
RECYCLING PROGRAM Qualifies for the Invista Reclamation Program

WARRANTIES:

WEAR WARRANTY	Useful Life
STATIC WARRANTY	Useful Life
EDGE RAVEL GUARANTEE	Useful Life
DELAMINATION GUARANTEE	Useful Life

CRI Green Label Plus Indoor Air Quality Testing Program - Passes - Certification No. GLP 2878

NOTES:

Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber, fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture". Performance is not affected by these variables

Shading is the result of crushed pile in usage and oftentimes is described as water marking. Since this is an inherent characteristic of all fine cut pile and cut/loop pile carpets, it does not constitute a manufacturing defect.

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step® Walk-Off Tiles by Blue Ridge or Walk-off mats are recommended at building entryways to reduce soiling.

Carpet should be installed according to manufacturer's carpet installation procedures.