

Effective Date: November 18, 2004

*SPECIFICATIONS

QUALITY: H-340 HERCULES - Power-Lock® High Performance Backing System

COLORS:	2630 Crete	2633 Temple	2636 Galaxy
	2631 Warrior	2634 Hero	2637 Stadium
	2632 Delphi	2635 Pegasus	2638 Justice

CONSTRUCTION	-	Stitch Lock™ Technology – Minimum ¾” Step-Over
PILE FIBER	-	100% Zeftron Solure EnviroSix® Nylon contains a minimum of 25% recycled content. Treated with Blue Shield stain and a soil protector.
DYE METHOD	-	Solution Dyed
PRIMARY BACKING	-	100% Synthetic
SECONDARY BACKING	-	Power Lock® High Performance Backing System
YARN PLY	-	3 & 4 ply
TUFTED YARN WEIGHT	-	28 oz. per sq. yd. (949 g/m ²)
FINISHED PILE THICKNESS	-	.104 Inch Approx. (2.64 mm)
STITCHES PER INCH	-	9 (3.54 stitches/cm)
MACHINE GAUGE	-	1/8 (3.1 rows/cm)
DENSITY FACTOR	-	9,692
TRAFFIC CLASS	-	Extra Heavy Commercial Class III
CARPET WIDTH	-	12' (3.66 m)
DYE LOT SIZE	-	20,000 sq. yds.
VETTERMAN DRUM-WEAR	-	3-4 or better after 22,000 cycles - ASTM 5417
DELAMINATION	-	2.70 Lbs/Inch or Greater - ASTM D3936
LIGHT FASTNESS	-	4 or Better After 8 Cycles of Exposure - AATCC 16
OZONE	-	4 or Better After 8 Cycles of Exposure - AATCC 129
OXIDES OF NITROGEN	-	4 or Better After 8 Cycles of Exposure - AATCC 164
FLAMMABILITY	-	ASTM E-648 – Class I NFPA 258 – 450 or Less

WARRANTIES:

EDGE RAVEL GUARANTEE	-	Useful Life
DELAMINATION GUARANTEE	-	Useful Life
RUN RESISTANCE WARRANTY	-	Useful Life
WEAR WARRANTY	-	Useful Life
STAIN REMOVAL GUARANTEE	-	Useful Life
STATIC WARRANTY	-	Useful Life
COLORFASTNESS TO LIGHT	-	Useful Life
COLORFASTNESS TO ATMOSPHERIC CONTAMINANTS	-	Useful Life
RECYCLING PROGRAM	-	Qualifies for 6ix®

CRI – INDOOR AIR QUALITY TESTING PROGRAM – PASSES – CERTIFICATION NO. 16654078

NOTES:

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step walk-off tiles by Blue Ridge or walk-off mats are recommended at building entryways to reduce soiling.

*Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber, fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture". Performance is not affected by these variables.

Hercules, requires the row cut / trace cut seaming technique in order to produce quality seams. Seam sealer must be used.

Carpet must be installed according to manufacturer's carpet installation procedures.