

QUALITY: 2200 HOMECOMING

COLORS:	2201 Blackpool	2207 Blaze	2213 Whalebone	2219 Hide
	2202 Nightspur	2208 Copperhead	2214 Stargaze	2220 Ragweed
	2203 Terrain	2209 Tannery	2215 Satellite	2221 Highland
	2204 Barkwood	2210 Plumate	2216 Snowdrift	2222 Tree Moss
	2205 Axis	2211 Cogwheel	2217 Skyline	2223 Laurel
	2206 Sunrise	2212 Wheatmeal	2218 Bluebell	2224 Acre

CONSTRUCTION	-	Tufted Cut Pile
YARN	-	100% XTI BCF Nylon
YARN CONSTRUCTION	-	6.0 Turns Per Inch
TUFTED YARN WEIGHT	-	30 Ounces (1017 g/m ²)
MACHINE GAUGE	-	1/10" (3.94 rows/cm)
STITCHES PER INCH	-	8 (3.15 stitches/cm)
AVERAGE PILE HEIGHT	-	.143 (3.63mm)
DYE METHOD	-	Pressure Beck
SOIL / STAIN PROTECTION	-	Blue Shield® Soil and Stain Protector
DENSITY FACTOR	-	7,552
PRIMARY BACK	-	Woven Polypropylene
SECONDARY BACK	-	Woven Synthetic
RADIANT PANEL TEST	-	Class I
NBS SMOKE CHAMBER TEST	-	Passes
CUSTOM COLORS	-	60 Sq. Yd. Minimum. Contact mill for details.
COORDINATING STYLES	-	The Americana Series
OPTIONAL BACKINGS	-	High tuft-bind woven synthetic, moisture barrier backings and attached polyurethane cushions available. Contact mill for details.
WARRANTIES	-	10-Year Wear Warranty 10-Year Delamination Warranty 10-Year Edge Ravel Warranty

CRI Green Label Plus Indoor Air Quality Testing Program - Passes – Certification No. GLP 2878

NOTES:

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step® walk-off tiles or walk-off mats are recommended at building entryways to reduce soiling.

Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture." Performance is not affected by these variables.

Some visual inconsistencies in the surface appearance of all textile products should be expected, including visible seams. This product requires the row cut seaming technique in order to produce quality seams. Seam sealer must be used.

Carpet should be installed according to manufacturer's carpet installation procedures.