

Effective Date: September 17, 2003

*SPECIFICATIONS

QUALITY: H-605 HOPSCOTCH

COLORS:

2182 Gravel	2186 Eucalyptus	2190 Parchment	2194 Dune
2183 Silver Charcoal	2187 Mist	2191 Algae	2195 Sienna
2184 Celadon	2188 Oyster	2192 Taupe	2196 Port
2185 Walnut	2189 Fog	2193 Raisin	2197 Thistle

CONSTRUCTION	-	Multi-Level Pattern Loop
PILE FIBER	-	100% Antron® Legacy Nylon with Dura Tech Soil Resistance Treatment.
YARN PLY	-	2 Ply
TUFTED YARN WEIGHT	-	28 ozsa per sq. yd. (949 g/m ²)
MACHINE GAUGE	-	1/10" (3.94 rows/cm)
STITCHES PER INCH	-	13 (5.12 stitches/cm)
FINISHED TUFTED PILE THICKNESS	-	.160 inch approx. (4.06 mm)
DENSITY	-	6,300
PATTERN REPEAT	-	16" W x 16" L (40.64 cm W x 40.64 cm L)
WIDTH	-	12' (3.66m)
PRIMARY BACKING	-	100% Synthetic
SECONDARY BACKING	-	Power Lock® High Performance Backing
ASTM E-648	-	Average Critical Radiant Flux: Greater than .45 - Class 1
NBS SMOKE CHAMBER TEST	-	Specific Optical Density: Less than 450
COORDINATE PRODUCTS	-	Foundation

WARRANTIES:

Wear Warranty	-	10 Years
Static Warranty	-	Useful Life
Edge Ravel Guarantee	-	Useful Life
Delamination Guarantee	-	Useful Life
RECYCLING	-	Qualifies for the Invista Reclamation Program

CRI INDOOR AIR QUALITY TESTING PROGRAM – PASSES – CERTIFICATION NO. 14222878

NOTES:

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step walk-off tiles by Blue Ridge or walk-off mats are recommended at building entryways to reduce soiling.

*Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber, fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture". Performance is not affected by these variables.

As with all patterned carpet, a perfect pattern match may not be possible due to the fact that carpet is a textile subject to shrinking and expansion in both length and width. A plus or minus 1% should be expected. However, a reasonable pattern match may be achieved by competent installers using power stretching and stay nailing techniques.

Installation of pattern carpet requires more time to install correctly, which should be considered in the original installation quotation.