

**SPECIFICATIONS**

**QUALITY: H610 HORIZON**

<b>COLORS:</b>	9870 Charcoal Mist	9890 Lime Field	9910 Clay Pot
	9871 Nightstar	9891 Deep Viridian	9911 Brickware
	9872 Granite Stone	9892 Rolling Hill	9912 Woodstick
	9873 Peat	9893 Kingfisher	9913 Autumn Leaf
	9874 Forest Moss	9894 Chambray	9914 Cowslip
	9875 Dark Sage	9895 Purple Sky	9915 Morello
	9876 Smoke Cloud	9896 Windsor Blue	9916 Wild Chestnut
	9877 Grey Ash	9897 Duck Egg	9917 Fawn
	9878 Seaweed	9898 Mountain Spring	9918 Dried Straw
	9879 Bark Chip	9899 Cerulean Blue	9919 Goldenrod
	9880 Beeswax	9900 Haze	9920 Orchard
	9881 Sand Grain	9901 Deep Amethyst	9921 Buttercup
	9882 Farmland	9902 Wineberry	9922 Sun-kissed Wheat
	9883 Lichen	9903 Pale Taupe	9923 Paprika
	9884 Pistachio Nut	9904 Thistle	9924 String
	9885 Hunting Green	9905 Dark Mushroom	9925 Vanilla
	9886 Mustard Seed	9906 Cranapple	9926 Silver Birch
	9887 Old Glory	9907 Sepia	9927 Oatmeal
	9888 Frog Pond	9908 Nutmeg Spice	9928 Raw Linen
	9889 Heath Green	9909 Turmeric	9929 Pebble Beach

<b>CONSTRUCTION</b>	Solid Color Cut Pile
<b>YARN</b>	100% XTI BCF Nylon with Soil Resistance Treatment.
<b>YARN PLY</b>	2 Ply
<b>TUFTED YARN WEIGHT</b>	38 Ounces Per Sq. Yd.
<b>MACHINE GAUGE</b>	1/10 (3.94 rows/cm)
<b>STITCHES PER INCH</b>	10 (3.94 stitches/cm)
<b>FINISHED PILE THICKNESS</b>	.218 Inch Approx. (5.56 mm)
<b>DENSITY FACTOR</b>	6,275
<b>WIDTH</b>	12' (3.66 m)
<b>PRIMARY BACKING</b>	100% Synthetic
<b>SECONDARY BACKING</b>	Power Lock® RE with minimum 10% post consumer recycled content based on total product weight. Produced with LOMAX™ Technology, a renewable energy.
<b>FLAMMABILITY</b>	Flooring Radiant Panel Test ASTM E-648 – Passes Class I. NBS Smoke Chamber (NFDA 258). Has a Maximum Specific Optical Density of 450 or less.
<b>RECYCLING PROGRAM</b>	Qualifies for Blueridge Blue Cycle Reclamation Program
<b><u>WARRANTIES:</u></b>	
Wear Warranty	10 Year
Static Warranty	Useful Life
Edge Ravel Guarantee	Useful Life
Delamination Guarantee	Useful Life

**CRI Green Label Plus Indoor Air Quality Testing Program - Passes - Certification No. GLP 2878**

**NOTES:**

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean step walk-off tiles by Blue Ridge or walk-off mats are recommended at building entryways to reduce soiling.

Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber, fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture". Performance is not affected by these variables.

Shading is the result of crushed pile in usage and oftentimes is described as water marking. Since this is an inherent characteristic of all fine cut pile and cut/loop pile carpets, it does not constitute a manufacturing defect.

Carpet should be installed according to manufacturer's carpet installation procedures. Seam sealer must be used.