

**SPECIFICATIONS**

**QUALITY: 9300 LANDSCAPE**

<b>COLORS:</b>	9301 Hot Spring	9305 Koi Pond	9309 Rugged Shore
	9302 Sandbar	9306 Timbercrest	9310 Spanish Moss
	9303 Volcano	9307 Everglade	9311 Rushing Water
	9304 Tundra	9308 English Garden	9312 Wetland

- CONSTRUCTION** - Dyna-Tronics Loop Pattern
- YARN CONTENT** - 100% SEP\* Nylon with Antistat
- YARN WEIGHT TUFTED** - 30 Oz. (1017 g/m<sup>2</sup>)
- GAUGE** - 1/12" (4.72 rows/cm)
- STITCHES PER INCH** - 13 (5.11 stitches/cm)
- FINISHED PILE THICKNESS** - .160 (4.06 mm)
- DYE METHOD** - 87% Solution Dyed / 13% Space Dyed
- SOIL / STAIN PROTECTION** - Blue Shield® Soil and Stain Protector
- DENSITY** - 6,967
- PRIMARY BACKING** - Woven Polypropylene
- SECONDARY BACKING** - Woven Synthetic
- RADIANT PANEL TEST** - Class I
- PATTERN REPEAT** - 24" W x 30" L (60.96 cm W x 76.2 cm L)
- NBS SMOKE CHAMBER TEST** - Passes
- RECYCLING PROGRAM** - Qualifies for Blueridge Blue Cycle Reclamation Program
- OPTIONAL BACKINGS** - High tuft-bind woven synthetic, polyurethane attached cushion and others are available for normal upcharges.
- WARRANTIES** - 10-Year Wear Warranty  
10-Year Delamination Warranty  
10-Year Edge Ravel Warranty

**CRI Green Label Plus Indoor Air Quality Testing Program – Passes – Certification No. GLP 4078**

**NOTES:**

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step® walk-off tiles or walk-off mats are recommended at building entryways to reduce soiling.

Specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber, temperature, and humidity, and may vary within normal industry tolerances. Performance is not affected by such variables.

Some visual inconsistencies in the surface appearance of all textile products should be expected, including visible seams. This product requires the row cut seaming technique in order to produce quality seams. Seam sealer must be used.

Carpet should be installed according to manufacturer's carpet installation procedures.

\*S.E.P. Nylon is: Solution dyed/Space dyed Environmentally Positive nylon by Richmond Carpet Company. SEP nylon is produced using environmentally friendly pigments and is recyclable.