

SPECIFICATIONS

QUALITY: 5400 LIGHTS

COLORS (9): 5402 Ambient 5406 Lantern
5403 Radiant 5407 Twinkle
5404 Sconce 5408 Glimmer
5405 Afterglow 5409 Twilight

- CONSTRUCTION** - Multi-Level Pattern Loop
- YARN** - 100% SEP* Nylon with Antistat
- TUFTED YARN WEIGHT** - 24 Ounces (814g/m²)
- MACHINE GAUGE** - 1/12" (4.72 rows/cm)
- STITCHES PER INCH** - 12 (4.72 stitches/cm)
- FINISHED PILE THICKNESS** - .152" (3.86mm)
- WIDTH** - 12 ft. (3.66 m)
- DYE METHOD** - 66% Solution Dyed / 34% Space Dyed
- SOIL/STAIN PROTECTION** - Blue Shield® Soil and Stain Protector
- DENSITY** - 5684
- CRI TRAFFIC RATING** - Heavy
- SECONDARY BACKING** - Woven Synthetic
- RADIANT PANEL TEST** - Class I
- NBS SMOKE CHAMBER TEST** - Passes
- COORDINATING STYLES** - Sounds, Homecoming
- PATTERN REPEAT** - ¼" W (.635 cm W)
- RECYCLING PROGRAM** - Qualifies for Blueridge Blue Cycle Reclamation Program
- OPTIONAL BACKINGS** - High tuft-bind woven synthetic, moisture barrier backings and attached polyurethane cushions available. Contact mill for details.
- WARRANTIES** - 10-Year Wear Warranty
10-Year Delamination Warranty
10-Year Edge Ravel Warranty

CRI Green Label Plus Indoor Air Quality Testing Program - Passes – Certification No. GLP 4078

NOTES:

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step® walk-off tiles or walk-off mats are recommended at building entryways to reduce soiling.

Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture." Performance is not affected by these variables.

Some visual inconsistencies in the surface appearance of all textile products should be expected, including visible seams. This product requires the row cut seaming technique in order to produce quality seams. Seam sealer must be used.

Carpet should be installed according to manufacturer's carpet installation procedures.

*S.E.P. Nylon is: Solution dyed/Space dyed Environmentally Positive nylon by Richmond Carpet Company. SEP nylon is produced using environmentally friendly pigments and is recyclable.