

Effective Date: September 17, 2003

\*SPECIFICATIONS

QUALITY: L-350 LINE DANCE

|         |                |              |               |             |
|---------|----------------|--------------|---------------|-------------|
| COLORS: | 2125 Parchment | 2129 Algae   | 2133 Lavender | 2137 Dune   |
|         | 2126 Fog       | 2130 Laurel  | 2134 Thistle  | 2138 Gravel |
|         | 2127 Oyster    | 2131 Mist    | 2135 Eggplant | 2139 Walnut |
|         | 2128 Taupe     | 2132 Celadon | 2136 Sienna   | 2140 Java   |

|                         |   |   |
|-------------------------|---|---|
| CONSTRUCTION            | - | Enhanced Precision Cut and Uncut                                      |
| PILE FIBER              | - | 100% Antron Legacy Nylon with<br>Dura Tech Soil Resistance Treatment. |
| YARN PLY                | - | 2 Ply   |
| TUFTED YARN WEIGHT      | - | 32 ozs. per sq. yd. (1085 g/m <sup>2</sup> )                          |
| MACHINE GAUGE           | - | 1/8" (3.15 rows/cm)   |
| STITCHES PER INCH       | - | 13 (5.12 stitches/cm)   |
| FINISHED PILE THICKNESS | - | .229 Inch Approx. (5.81 mm)   |
| DENSITY FACTOR          | - | 5,031   |
| WIDTH                   | - | 12' (3.66m)   |
| PRIMARY BACKING         | - | 100% Synthetic  |
| SECONDARY BACKING       | - | Power Lock® High Performance Backing                                  |
| ASTM E-648              | - | Average Critical Radiant Flux: Greater than<br>.45 - Class 1          |
| NBS SMOKE CHAMBER TEST  | - | Specific Optical Density: Less than 450                               |
| COORDINATE PRODUCTS     | - | Foundation  |

WARRANTIES:

|                         |   |   |
|-------------------------|---|---|
| Wear Warranty           | - | 10 Year                                       |
| Static Warranty         | - | Useful Life                                   |
| Edge Ravel Guarantee    | - | Useful Life                                   |
| Delamination Guarantee  | - | Useful Life                                   |
| Run Resistance Warranty | - | Useful Life                                   |
| Recycling Programs      | - | Qualifies for the Invista Reclamation Program |

CRI INDOOR AIR QUALITY TESTING PROGRAM – PASSES – CERTIFICATION NO. 14222878

NOTES:

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step walk-off tiles by Blue Ridge or walk-off mats are recommended at building entryways to reduce soiling.

\*Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber, fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture". Performance is not affected by these variables.

As with all patterned carpet, a perfect pattern match may not be possible due to the fact that carpet is a textile subject to shrinking and expansion in both length and width. A plus or minus 1% should be expected. However, a reasonable pattern match may be achieved by competent installers using power stretching and stay nailing techniques.

Installation of pattern carpet requires more time to install correctly, which should be considered in the original installation quotation.