

Effective Date: August 8, 2007

***SPECIFICATIONS**

QUALITY: M185 MARATHON

COLORS: (25)	2764 Praline	2777 Sierra Canyon	2814 Buff	2831 Winsome
	2766 Essence	2785 Mojito	2816 Macadamia	2833 Serene
	2768 Lemongrass	2786 Waterfall	2819 Biscuit	2834 Cannon Gray
	2769 Mosstone	2788 Evergreen	2824 Cool Mist	2836 Mineralite
	2770 Copperidge	2799 Serape	2825 Bashful	2837 Stormcloud
	2776 Hickory	2802 Sangria	2828 Envy	2838 Smokewood
				2839 Silversmith

CONSTRUCTION	Multi-Level Patterned Loop
PILE FIBER	100% Antron Legacy Nylon featuring Invista® Soie and Merino Fiber <i>Effects</i> ™.
SOIL TREATMENT	DuraTech® Soil Resistance Treatment
BENEFITS	Antron® Legacy carpet face fiber has been certified by Scientific Certification Systems as an Environmentally Preferable Product.
TUFTED YARN WEIGHT	30 Ounces Per Sq. Yd. (1017 g/m ²)
MACHINE GAUGE	1/10" (3.94 rows/cm)
STITCHES PER INCH	8 (3.15 stitches/cm)
FINISHED PILE THICKNESS	.176 Inch Approx. (4.47 mm)
DENSITY FACTOR	6136
WIDTH	12' (3.66m)
PRIMARY BACKING	100% Synthetic
SECONDARY BACKING	Power Lock® RE w/ minimum 10% post consumer recycled content based on total product weight
ASTM E-648	Average Critical Radiant Flux: Greater than .45 - Class 1
NBS SMOKE CHAMBER TEST	Specific Optical Density: Less than 450
COORDINATE PRODUCTS	Great Inspirations, Camaraderie Collection, Art & Soul Collection, Gatsby Collection, Artful Endeavors
PATTERN REPEAT	¾" W x ¾" L (1.91 cm W x 1.91 cm L)
CUSTOM COLORS	Available 60 Sq. Yd. Min per Color
RECYCLING PROGRAM	Qualifies for the Invista™ Carpet Reclamation Program
WARRANTIES:	
WEAR WARRANTY	10 Year
STATIC WARRANTY	Useful Life
EDGE RAVEL GUARANTEE	Useful Life
DELAMINATION GUARANTEE	Useful Life

CRI Green Label Plus Indoor Air Quality Testing Program - Passes - Certification No. GLP 2878

NOTES:

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step® Walk-Off Tiles by Blue Ridge or Walk-off mats are recommended at building entryways to reduce soiling.

Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber, fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture". Performance is not affected by these variables

Due to the nature of patterned textile products, an exact pattern match cannot be guaranteed. Some visual inconsistencies in the surface appearance of all textile products should be expected, including visible seams. This product, Marathon, requires the row cut seaming technique in order to product quality seams. Patterned carpet may require special attention by the installer to assure a suitable match and must be addressed in the original labor quotation. Seam sealer must be used. Carpet must be installed according to manufacturer's installation procedures.