

**\*SPECIFICATIONS**

**QUALITY:**       **M350T MERCURY 24" X 24" EnviroFlex® Carpet Tile**  
**M350V MERCURY 6 Ft. EnviroFlex® Vinyl**

**COLORS:**       2441 Heat                       2445 Element  
                   2442 Explosive               2446 Liquid  
                   2443 Electric                   2447 Metal  
                   2444 Power                     2448 Rays

- CONSTRUCTION**               -       Multi-Level Pattern Loop
- YARN**                               -       66% Solution Dyed Nylon / 34% Yarn Dyed Nylon
- DYE METHOD**                   -       Solution Dyed / Yarn Dyed
- PRIMARY BACKING**           -       100% Synthetic
- SECONDARY BACKING**       -       EnviroFlex® Performance Engineered Backing w/40% Recycled Content
- YARN PLY**                       -       2 Ply
- TUFTED YARN WEIGHT**       -       18 Ounces Per Sq. Yd. (610 g/m<sup>2</sup>)
- FINISHED PILE THICKNESS**   -       Approximately .081 inch (2.06 mm)
- STITCHES PER INCH**           -       9 (3.54 stitches/cm)
- MACHINE GAUGE**             -       1/10" (3.94 rows/cm)
- DENSITY**                       -       8000
- TILE SIZE**                     -       24" X 24" (60.96 cm X 60.96 cm)
- ROLL WIDTH**                  -       6 Ft. (1.83 cm)
- TRAFFIC CLASS**               -       Extra Heavy Commercial Class III
- FLAMMABILITY**               -       ASTM E648 – Class I
- ADHESIVE**                     -       BR200 EnviroFlex® Modular Carpet Adhesive
- PATTERN REPEAT**             -       Random
  
- Installation                   -       Monolithic or Checkerboard
- Wear Warranty                -       Useful Life
- Edge Ravel Guarantee       -       Useful Life
- Delamination Guarantee    -       Useful Life
- Run Resistance Warranty    -       Useful Life
- Static Warranty              -       Useful Life
- Recycling Program            -       Qualifies for Blueridge Blue Cycle Reclamation Program

**CRI Green Label Plus – Indoor Air Quality Testing Program – Passes – Certification No. GLP 9712**

**NOTES:**

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step® walk-off tiles or walk off mats are recommended at building entryways to reduce soiling.

Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture". Performance is not affected by these variables

Due to the nature of modular patterned textile products, an exact pattern match cannot be guaranteed. Some visual inconsistencies in the surface appearance of all textile products should be expected, including visible seams.

Carpet should be installed according to manufacturer's carpet installation procedures.