

**SPECIFICATIONS**

**QUALITY: M500 MIRADA CLASSICS**

<b>COLORS:</b>	2716 Castle Gray	2722 Spun Gold	2728 Sunrise	2734 Brook
	2717 Aurora	2723 Ancient Oak	2729 Tavern	2735 Denim
	2718 Winter Field	2724 Dawn	2730 Fireball	2736 Morning Light
	2719 Rock Garden	2725 Dragonfly	2731 Ruby	2737 Blue Lagoon
	2720 Flax	2726 Thicket	2732 Amethyst	2738 Crystal
	2721 Chariot	2727 Emerald	2733 Sapphire	2739 Falcon

CONSTRUCTION	Stitch Lock™ Technology
PILE FIBER	100% Antron® Lumena Solution Dyed Nylon with Duratech® Soil Resistant Treatment
DYE METHOD	Solution Dyed
BENEFITS	Antron® Lumena solution dyed nylon carpet face fiber has a 30% lower total environmental impact than typical industry. Duratech® soil resistant treatment provides superior soil resistance durable for the useful life of the carpet.
PRIMARY BACKING	100% Synthetic
SECONDARY BACKING	Power Lock® RE with minimum 10% post consumer recycled content based on total product weight. Produced with LOMAX™ Technology, a renewable energy.
TUFTED YARN WEIGHT	28 Oz. per Sq. Yd. (949 g/m²)
FINISHED PILE THICKNESS	.133 Inch approx. (3.38 mm)
DENSITY	7579
STITCHES PER INCH	10 (3.94 stitches/cm)
MACHINE GAUGE	1/8 (3.1 rows/cm)
CRI TRAFFIC RATING	Severe
CARPET WIDTH	12' (3.66 m)
DYE LOT SIZE	20,000 Square Yards
FLAMMABILITY	ASTM E-648 – Class I NFPA 258 – 450 or Less
RECYCLING PROGRAM	Qualifies for Blueridge Blue Cycle Reclamation Program

**WARRANTIES:**

EDGE RAVEL GUARANTEE	Useful Life
DELAMINATION GUARANTEE	Useful Life
RUN RESISTANCE WARRANTY	Useful Life
WEAR WARRANTY	Useful Life
STAIN REMOVAL GUARANTEE	Useful Life
STATIC WARRANTY	Useful Life
COLORFASTNESS TO LIGHT	10 Year
COLORFASTNESS TO ATMOSPHERIC CONTAMINANTS	5 Year

**CRI Green Label Plus Indoor Air Quality Testing Program - Passes - Certification No. GLP 4078**

**NOTES:**

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step® walk-off tiles by Blue Ridge or walk-off mats are recommended at building entryways to reduce soiling.

Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber, fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture". Performance is not affected by these variables.

Due to the nature of patterned textiles products, an exact pattern match cannot be guaranteed. Some visual inconsistencies in the surface appearance of all textile products should be expected, including visible seams. This product requires the row cut seaming technique in order to produce quality seams. Seam sealer must be used.

Carpet must be installed according to manufacturer's carpet installation procedures.