

SPECIFICATIONS

QUALITY: M367 MIRADA IV

COLORS:	9113 Blue Gemstone	9117 Tapestry Teal	9123 Umberlite	9127 Moonsand
	9114 Peritwinkle	9119 Greenland	9124 Mystic Shadow	
	9115 Columbia Blue	9120 Dark Opal	9125 Caravelle Red	
	9116 Islandia	9121 Starfire	9126 Fired Copper	

CONSTRUCTION	Tufted Step-Over Stitch - Minimum 3/4" Step-Over
PILE FIBER	100% Zeftron Solure enviro6ix® Nylon contains a minimum of 25% recycled content. Treated with Blue Shield® stain and soil protector.
DYE METHOD	Solution Dyed
PRIMARY BACKING	100% Synthetic
SECONDARY BACKING	Power Lock® RE with minimum 10% post consumer recycled content based on total product weight. Produced with LOMAX™ Technology, a renewable energy.
YARN PLY	4 Ply
TUFTED YARN WEIGHT	28 Oz. per Sq. Yd. (949 g/m²)
FINISHED PILE THICKNESS	.120 Inch Approx. (3.05 mm)
STITCHES PER INCH	8 (3.15 stitches/cm)
MACHINE GAUGE	1/8" (3.15 rows/cm)
DENSITY FACTOR	8,400
TRAFFIC CLASS	Extra Heavy Commercial Class III
CARPET WIDTH	12' (3.66 m)
DYE LOT SIZE	20,000 Square Yards
RUN RESISTANCE	20 Pounds - Test PT-155
VETTERMAN DRUM-WEAR	3-4 or better after 22,000 cycles - ASTM 5417
DELAMINATION	2.70 Lbs/Inch or Greater - ASTM D3936
LIGHT FASTNESS	4 or Better After 8 Cycles of Exposure - AATCC 16
OZONE	4 or Better After 8 Cycles of Exposure - AATCC 129
OXIDES OF NITROGEN	4 or Better After 8 Cycles of Exposure - AATCC 164
FLAMMABILITY	Flooring Radiant Panel Test ASTM E-648 - Passes – Class I. NBS Smoke Chamber (NFDA 258). Has a Maximum Specific Optical Density of 450 or less.
RECYCLING PROGRAM	Qualifies for Blueridge Blue Cycle Reclamation Program

WARRANTIES:

EDGE RAVEL GUARANTEE	Useful Life
DELAMINATION GUARANTEE	Useful Life
RUN RESISTANCE WARRANTY	Useful Life
WEAR WARRANTY	Useful Life
STAIN REMOVAL GUARANTEE	Useful Life
STATIC WARRANTY	Useful Life
COLORFASTNESS TO LIGHT	Useful Life
COLORFASTNESS TO ATMOSPHERIC CONTAMINANTS	Useful Life

CRI Green Label Plus Indoor Air Quality Testing Program - Passes - Certification No. GLP 4078

NOTES:

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step walk-off tiles by Blue Ridge or walk-off mats are recommended at building entryways to reduce soiling.

Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber, fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture". Performance is not affected by these variables.

Carpet must be installed according to manufacturer's carpet installation procedures. Seam sealer must be used.