

SPECIFICATIONS

QUALITY: M368 MIRADA V

COLORS: 9686 Burnished Pewter 9690 River Rock 9694 Flat Iron 9698 Coal Dust
9687 Midas Touch 9691 Glen Eden 9695 Aspen Bark 9699 Baroque Plum
9688 Ginger Brickel 9692 Tresco Teal 9696 Gridwork 9700 Copper Foil
9689 Aged Metal 9693 Normandy 9697 Lone Star Blue 9701 Rococo Silk

CONSTRUCTION Tufted Step-Over Stitch - Minimum 3/4" Step-Over
PILE FIBER 100% Zeftron Solure enviro6ix® Nylon contains a minimum of 25% recycled content. Treated with Blue Shield® stain and soil protector.

DYE METHOD Solution Dyed
PRIMARY BACKING 100% Synthetic
SECONDARY BACKING Power Lock® RE with minimum 10% post consumer recycled content based on total product weight. Produced with LOMAX™ Technology, a renewable energy.

YARN PLY 3 Ply
TUFTED YARN WEIGHT 28 Oz. per Sq. Yd. (949 g/m²)
FINISHED PILE THICKNESS .124 Inch Approx. (3.15 mm)
STITCHES PER INCH 10 (3.94 stitches/cm)
MACHINE GAUGE 1/8" (3.15 rows/cm)
DENSITY FACTOR 8,129
TRAFFIC CLASS Extra Heavy Commercial Class III
CARPET WIDTH 12' (3.66 m)
DYE LOT SIZE 20,000 Square Yards
RUN RESISTANCE 20 Pounds - Test PT-155
VETTERMAN DRUM-WEAR 3-4 or better after 22,000 cycles - ASTM 5417
DELAMINATION 2.70 Lbs/Inch or Greater - ASTM D3936
LIGHT FASTNESS 4 or Better After 8 Cycles of Exposure - AATCC 16
OZONE 4 or Better After 8 Cycles of Exposure - AATCC 129
OXIDES OF NITROGEN 4 or Better After 8 Cycles of Exposure - AATCC 164
FLAMMABILITY Flooring Radiant Panel Test ASTM E-648 - Passes – Class I.
NBS Smoke Chamber (NFDA 258). Has a Maximum Specific Optical Density of 450 or less.

WARRANTIES:

EDGE RAVEL GUARANTEE	Useful Life
DELAMINATION GUARANTEE	Useful Life
RUN RESISTANCE WARRANTY	Useful Life
WEAR WARRANTY	Useful Life
STAIN REMOVAL GUARANTEE	Useful Life
STATIC WARRANTY	Useful Life
COLORFASTNESS TO LIGHT	Useful Life
COLORFASTNESS TO ATMOSPHERIC CONTAMINANTS	Useful Life
RECYCLING PROGRAM	Qualifies for Blueridge Blue Cycle Reclamation Program

CRI Green Label Plus Indoor Air Quality Testing Program - Passes - Certification No. GLP4078

NOTES:

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step walk-off tiles by Blue Ridge or walk-off mats are recommended at building entryways to reduce soiling.

Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber, fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture". Performance is not affected by these variables. The density factor and weight density factor are calculated on a theoretical basis and they will vary. They are not subject to tolerance limitations.

Carpet must be installed according to manufacturer's carpet installation procedures. Seam sealer must be used.