

Effective Date: March 17, 2000

*SPECIFICATIONS

QUALITY: M-369 MIRADA VI – Synthetic PowerLock® Backing System

COLORS:	9690 River Rock	9693 Normandy	9696 Gridwork
	2015 Thistledown	2016 Meadowlark	2018 Country Tweed
	2019 Rocky Road	2021 Fjord	2022 Pepper Sauce
	2023 Sycamore	9687 Midas Touch	9698 Coal Dust

CONSTRUCTION	-	Stitch Lock™ Technology
PILE FIBER	-	100% Zeftron® Solure Nylon containing recycled content. Treated with a stain protector and a soil repellent.
DYE METHOD	-	Solution Dyed
PRIMARY BACKING	-	100% Synthetic
SECONDARY BACKING	-	PowerLock® 20 System
YARN PLY	-	3 Ply
TUFTED YARN WEIGHT	-	28 oz. per sq. yd. (9.49 g/m ²)
FINISHED PILE THICKNESS	-	.124 inch approx. (3.15 mm)
STITCHES PER INCH	-	10 (3.94 stitches/cm)
MACHINE GAUGE	-	1/8" (3.1 rows/cm)
DENSITY FACTOR	-	8,129
TRAFFIC CLASS	-	Extra Heavy Commercial Class III
CARPET WIDTH	-	12" (3.66 m)
TOTAL WEIGHT	-	72 oz. per sq. yd. approx.
DYE LOT SIZE	-	20,000 square yards
RUN RESISTANCE	-	20 lbs. – Test PT-155
VETTERMAN DRUM-WEAR	-	3-4 or better after 22,000 cycles – ASTM 5417