

**SPECIFICATIONS**

**QUALITY: M369 MIRADA VI**

**COLORS:**

9690 River Rock	2014 Hillcrest	2018 Country Tweed	2022 Pepper Sauce
9693 Normandy	2015 Thistledown	2019 Rocky Road	2023 Sycamore
9695 Aspen Bark	2016 Meadowlark	2020 Brigade	9687 Midas Touch
9696 Gridwork	2017 Berber Moss	2021 Fjord	9697 Lone Star Blue
			9698 Coal Dust

<b>CONSTRUCTION</b>	Stitch Lock™ Technology – Minimum ¾” Step-Over
<b>PILE FIBER</b>	100% Zeftron Solure enviro6ix® Nylon contains a minimum of 25% recycled content. Treated with Blue Shield® stain and soil protector.
<b>DYE METHOD</b>	Solution Dyed
<b>PRIMARY BACKING</b>	100% Synthetic
<b>SECONDARY BACKING</b>	Power Lock® RE with minimum 10% post consumer recycled content based on total product weight. Produced with LOMAX™ Technology, a renewable energy.
<b>YARN PLY</b>	3 Ply
<b>TUFTED YARN WEIGHT</b>	28 Oz. per Sq. Yd. (949 g/m²)
<b>FINISHED PILE THICKNESS</b>	.124 Inch Approx. (3.15 mm)
<b>STITCHES PER INCH</b>	10 (3.94 stitches/cm)
<b>MACHINE GAUGE</b>	1/8" (3.1 rows/cm)
<b>DENSITY FACTOR</b>	8,129
<b>TRAFFIC CLASS</b>	Extra Heavy Commercial Class III
<b>CARPET WIDTH</b>	12' (3.66 m)
<b>TOTAL WEIGHT</b>	72 Oz. Per Sq. Yd. Approx.
<b>DYE LOT SIZE</b>	20,000 Square Yards
<b>RUN RESISTANCE</b>	20 Pounds - Test PT-155
<b>VETTERMAN DRUM-WEAR</b>	3-4 or better after 22,000 cycles - ASTM 5417
<b>DELAMINATION</b>	2.70 Lbs/Inch or Greater - ASTM D3936
<b>LIGHT FASTNESS</b>	4 or Better After 8 Cycles of Exposure - AATCC 16
<b>OZONE</b>	4 or Better After 8 Cycles of Exposure - AATCC 129
<b>OXIDES OF NITROGEN</b>	4 or Better After 8 Cycles of Exposure - AATCC 164
<b>FLAMMABILITY</b>	ASTM E-648 – Class I NFPA 258 – 450 or Less

<b>WARRANTIES:</b>	
EDGE RAVEL GUARANTEE	Useful Life
DELAMINATION GUARANTEE	Useful Life
RUN RESISTANCE WARRANTY	Useful Life
WEAR WARRANTY	Useful Life
STAIN REMOVAL GUARANTEE	Useful Life
STATIC WARRANTY	Useful Life
COLORFASTNESS TO LIGHT	Useful Life
COLORFASTNESS TO ATMOSPHERIC CONTAMINANTS	Useful Life
RECYCLING PROGRAM	Qualifies for Blueridge Blue Cycle Reclamation Program

**CRI Green Label Plus Indoor Air Quality Testing Program - Passes - Certification No. GLP 4078**

**NOTES:**  
Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step walk-off tiles by Blue Ridge or walk-off mats are recommended at building entryways to reduce soiling.

Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber, fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture". Performance is not affected by these variables.

Mirada VI requires the row cut / trace cut seaming technique in order to produce quality seams. Seam sealer must be used.

Carpet must be installed according to manufacturer's carpet installation procedures.