

Revised
 Effective Date: February 1, 2003

*SPECIFICATIONS

QUALITY: M369T MIRADA VI – 24" x 24" Carpet Tile

COLORS:	9690 River Rock	9693 Normandy	9696 Gridwork
	2015 Thistledown	2016 Meadowlark	2018 Country Tweed
	2019 Rocky Road	2021 Fjord	2022 Pepper Sauce
	2023 Sycamore	9687 Midas Touch	9698 Coal Dust

CONSTRUCTION	-	Stitch Lock™ Technology
PILE FIBER	-	100% Zeftron® Solure Nylon contains recycled content. Treated with BlueShield® stain protector and a soil repellent.
DYE METHOD	-	Solution Dyed
PRIMARY BACKING	-	100% Synthetic
SECONDARY BACKING	-	EnviroFlex® Performance Engineered Backing with 40% recycled content
YARN PLY	-	3 Ply
TUFTED YARN WEIGHT	-	28 oz. per sq. yd. (949 m ²)
TOTAL WEIGHT	-	152 oz. per sq. yd. (5153 g/m ²)
FINISHED PILE THICKNESS	-	.124 inch approx. (3.15mm)
STITCHES PER INCH	-	10 (3.94 stitches/cm)
MACHINE GAUGE	-	1/10"
DENSITY FACTOR	-	8,129
TRAFFIC CLASS	-	Extra Heavy Commercial Class III
SIZE	-	24" x 24" (60.96cm x 60.96cm)
FLOORING RADIANT PANEL	-	ASTM E-648 – Class 1
SMOKE DENSITY	-	NFPA 258 – Passes
DYE LOT SIZE	-	20,000 square yards
VETTERMAN DRUM-WEAR	-	3-4 or better after 22,000 cycles – ASTM 5417
LIGHT FASTNESS	-	4 or better after 8 cycles of exposure – AATCC 16
OZONE	-	4 or better after 8 cycles of exposure – AATCC 129
OXIDES OF NITROGEN	-	4 or better after 8 cycles of exposure – AATCC 164
FLOORING RADIANT PANEL	-	ASTM E-648 – Class I
SMOKE DENSITY	-	NFPA 258 – Passes
ADHESIVE	-	BR200 Modular Carpet Adhesive