

SPECIFICATIONS

QUALITY: M370T MODERN 24" X 24" Carpet Tile

COLORS: 2351 Saarinen 2354 Deco Gray 2357 Realist Beige
2352 Industry Coal 2355 Abstract Tan 2358 Klee Brown
2353 Picasso Blue 2356 Cubists Rust 2359 Noveau Green

CONSTRUCTION - Multi-Level Pattern Loop
YARN - 100% Zeftron® Solure Nylon contains recycled content.
Treated with Blue Shield® stain and soil protector.
DYE METHOD - Solution Dyed
PRIMARY BACKING - 100% Synthetic
SECONDARY BACKING - EnviroFlex® Performance Engineered Backing w/40% Recycled Content
YARN PLY - 2 Ply
TUFTED YARN WEIGHT - 20 Ounces Per Sq. Yd. (678 g/m²)
TOTAL WEIGHT - 144 Ounces Per Sq. Yd. (4883 g/m²)
AVG.TUFTED PILE HEIGHT - Approximately .106 inch (2.69 mm)
STITCHES PER INCH - 10 (3.94 stitches/cm)
MACHINE GAUGE - 1/12" (4.72 rows/cm)
DENSITY - 6792
TILE SIZE - 24" X 24" (60.96 cm X 60.96 cm)
FLOORING RADIANT PANEL - ASTM E-648 – Class 1
SMOKE DENSITY - NFPA 258 - Passes
TRAFFIC CLASS - Extra Heavy Commercial Class III
DYE LOT SIZE - Up to 20,000 Square Yards
ADHESIVES - BR200 EnviroFlex® Modular Carpet Adhesive

Installation - Monolithic, ¼ Turn
Wear Warranty - Useful Life
Edge Ravel Guarantee - Useful Life
Delamination Guarantee - Useful Life
Run Resistance Warranty - Useful Life
Stain Removal Guarantee - Useful Life
Static Warranty - Useful Life
Colorfastness to Light - Useful Life
Colorfastness to Atmospheric Contaminants - Useful Life
Recycling Program - Qualifies for Blueridge Blue Cycle Reclamation Program

CRI Green Label Plus – Indoor Air Quality Testing Program – Passes – Certification No. GLP 9712

NOTES:

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step® walk-off tiles or walk-off mats are recommended at building entryways to reduce soiling.

Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture". Performance is not affected by these variables

Due to the nature of modular patterned textile products, an exact pattern match cannot be guaranteed. Some visual inconsistencies in the surface appearance of all textile products should be expected, including visible seams.

Carpet should be installed according to manufacturer's carpet installation procedures.