

Effective Date: June 22, 2007

SPECIFICATIONS*QUALITY: P311 PARALLELS**

COLORS: (16)	3057 Sassy	3061 Beau Beige	3065 Sagebrush	3069 Aspen
	3058 Buttercream	3062 It's Thyme	3066 Jasper	3070 Regent
	3059 So Sari	3063 Ginger	3067 Napa	3071 Meteor
	3060 Spiceberry	3064 Gretna Green	3068 Vista	3072 Soulful

CONSTRUCTION	Blue Sky® Technology – Tip Sheared
PILE FIBER	100% Antron Legacy Nylon with DuraTech® Soil Resistance Treatment.
BENEFITS	DuraTech® soil resistant treatment provides superior soil resistance durable for the useful life of the carpet. Antron® Legacy carpet face fiber has a 30% lower Total Environmental Impact than typical industry.
TUFTED YARN WEIGHT	32 Ounces Per Sq. Yd. (1085 g/m ²)
YARN PLY	2 Ply Heatset
MACHINE GAUGE	1/12" (4.72 rows/cm)
STITCHES PER INCH	12.5 (4.92 stitches/cm)
FINISHED PILE THICKNESS	.173 Inch Approx. (4.39 mm)
DENSITY FACTOR	6659
WIDTH	12' (3.66m)
PRIMARY BACKING	100% Synthetic
SECONDARY BACKING	Power Lock® RE w/ minimum 10% post consumer recycled content based on total product weight
ASTM E-648	Average Critical Radiant Flux: Greater than .45 - Class 1
NBS SMOKE CHAMBER TEST	Specific Optical Density: Less than 450
COORDINATE PRODUCTS	Marathon, Great Inspirations
PATTERN REPEAT	18" W x 25" L (45.72 cm W x 63.5 cm L)
CUSTOM COLORS	Available 60 Sq. Yd. Min per Color
RECYCLING PROGRAM	Qualifies for the Invista™ Carpet Reclamation Program

WARRANTIES:

WEAR WARRANTY	10 Year
STATIC WARRANTY	Useful Life
EDGE RAVEL GUARANTEE	Useful Life
DELAMINATION GUARANTEE	Useful Life

CRI Green Label Plus Indoor Air Quality Testing Program - Passes - Certification No. GLP 2878**NOTES:**

Chair pads are recommended under office chairs with roller casters to preserve appearance retention, act as a deterrent toward delamination and to avoid premature or accelerated wear. Clean Step® Walk-Off Tiles by Blue Ridge or Walk-off mats are recommended at building entryways to reduce soiling.

Product specifications are derived from averages resulting from normal manufacturing tolerances in yarn, fiber, fabrication or finishing, and may vary within normal industry tolerances. Construction value quotes are "at point of manufacture". Performance is not affected by these variables

Due to the nature of patterned textile products, an exact pattern match cannot be guaranteed. Some visual inconsistencies in the surface appearance of all textile products should be expected, including visible seams. This product, Parallels, requires the row cut seaming technique in order to produce quality seams. Seam sealer must be used. Carpet must be installed according to manufacturer's installation procedures.